

Huawei NetEngine AR8000 Series Enterprise Router Data Sheet

NetEngine AR8000 series enterprise routers are chassis-shaped routers designed by Huawei for enterprise headquarters and large branches. These routers offer a wide range of service features such as SD-WAN, routing, switching, and security, and come equipped with various interface types such as Ethernet, LTE/5G, E1, POS, and GPON/xGSPON, which allows them to deliver high performance and diversified services to meet the needs of different enterprises.

Product Overview

Huawei next-generation NetEngine AR8000 series enterprise routers are fitted with ARM multi-core processors and a non-blocking switching structure, delivering superior performance particularly when dealing with diverse and cloud-based services.

Huawei NetEngine AR8000 series enterprise routers are ideal for enterprise headquarters and large branches and can be deployed at the network egress as needed. This series consists of models such as NetEngine AR8140-12G10XG, NetEngine AR8140-T-12G10XG, and NetEngine AR8700-8, which can meet networking requirements of enterprises of different scales. In addition, they offer a variety of interface cards, such as Ethernet, LTE, E1, and POS, to help extend enterprise services.

- **Rich access capability:** Ethernet, LTE/5G (5G cards and 5G RUs), E1, POS, and GPON/xGSPON
- **High-quality SD-WAN:** fast ZTP, all-scenario networking architecture, application quality-based intelligent traffic steering, and WAN optimization, helping deliver ultimate service experience
- **Superior performance:** high-speed access of 5G RUs and service cards; built-in WAC capable of unified management of Wi-Fi 5/6/7 devices; seamless roaming between its connected APs
- **AI:** bandwidth planning, network orchestration, policy recommendation, in-band flow measurement, and automatic fault locating
- **Security protection:** integrates NGFW capabilities, offering multi-dimensional security policies, ASPF, application recognition and control, IPS, URL filtering, Antivirus, signature database and antivirus database update, and interconnection with third-party SSE security clouds
- **Reliability:** carrier-class hardware reliability, network-level high reliability, fast service fault recovery, and hot swapping supported
- **Easy O&M and management:** single-site ZTP within 10 minutes, batch site replication, SD-Branch LAN/WAN converged management, 5G RU and switch RU plug-and-play, digital map, visualized application quality and bandwidth, rights- and domain-based management, diversified alarm and log management methods, and report generation




NetEngineAR8140-12G10XG

- Fixed WAN ports*: 10 x 10GE SFP+, 8 x GE Combo, 4 x GE electrical
- 4 x SIC card
- Dimensions (H x W x D): 44.4 mm x 442.0 mm x 420.0 mm
- Dual power modules (AC/DC)



NetEngine AR8140-T-12G10XG

- Fixed WAN ports*: 10 x 10GE SFP+, 8 x GE Combo, 4 x GE electrical
- 4 x SIC card
- Dimensions (H x W x D): 44.4 mm x 442.0 mm x 420.0 mm

	<ul style="list-style-type: none"> • Dual power modules (AC/DC) • TPM
 <p>NetEngine AR8700-8</p>	<ul style="list-style-type: none"> • Fixed WAN ports*: 1 x 40GE QSFP+, 8 x 10GE SFP+, 8 x GE Combo • 8 x SIC card • Dimensions (H x W x D): 88.1 mm x 442.0 mm x 482.8 mm • Dual power modules (AC/DC) • Independent dual MPUs

*: Supported by all models: All fixed ports are LAN/WAN interchangeable.

Features and Highlights

Features and Highlights of NetEngine AR8000

Service Requirement	Feature and Highlight
High performance	<ul style="list-style-type: none"> • Integrates the ARM multi-core processor, NP network processor, hardware encryption/decryption engine, hardware TM engine, and hardware FEC codec engine, based on the self-developed SOC chip architecture. • Offers industry-leading performance, ensuring a low latency for mission-critical services. • Comes equipped with a high-performance multi-core processor that supports high-speed WAN connections and powerful route computing, improving L4–L7 service processing efficiency.
High reliability	<ul style="list-style-type: none"> • Provides backup links for enterprise services, enhancing service access reliability. • Detects link faults and completes route convergence in milliseconds, greatly shortening the service interruption time. • Comes equipped with dual MPUs (for AR8700 series only), ensuring zero video freezing during service switchovers.
Easy O&M	<ul style="list-style-type: none"> • Supports on-premises and cloud-based management by iMaster NCE-Campus using various protocols, such as NETCONF and SNMP, and high-performance data collection through telemetry. These help simplify network deployment, visualize O&M, and reduce OPEX.
SD-WAN	<ul style="list-style-type: none"> • Is ideal for the SD-WAN solution to build cost-effective and business-friendly connections over the Internet. • Supports application identification and link quality-based intelligent traffic steering, guaranteeing the experience of key applications. • Supports multi-link routing, dual-hub flexible networking, end-to-end IPsec encryption plus reliable devices, ensuring secure service transmission.
Architecture innovation	<ul style="list-style-type: none"> • Built-in WAC capable of unified management of Wi-Fi 5/6/7 devices; seamless roaming between its connected APs

Product Specifications

Features and Values of Huawei NetEngine AR8000 Series

Specifications	NetEngine AR8140-12G10XG NetEngine AR8140-T-12G10XG	NetEngine AR8700-8
System Parameters		
Forwarding performance (NAT+ACL+QoS, IMIX)	25 Gbps	30 Gbps
IPsec performance (IMIX)	20 Gbps	20 Gbps
IPsec performance (1420 bytes)	50 Gbps	50 Gbps
SD-WAN IPsec performance* (IMIX)	22 Gbps	24 Gbps
SD-WAN IPsec performance* (1400 bytes)	55 Gbps	60 Gbps
SD-WAN performance** (IMIX)	20 Gbps	20 Gbps
SD-WAN performance** (1400 bytes)	50 Gbps	40 Gbps
SD-WAN typical performance*** (IMIX)	15 Gbps	15.5 Gbps
SD-WAN typical performance*** (1400 bytes)	48 Gbps	40 Gbps
Fixed WAN ports	10 x 10GE SFP+, 8 x GE Combo, 4 x GE electrical (All WAN ports can be switched to LAN ports)	1 x 40GE QSFP+, 8 x 10GE SFP+, 8 x GE Combo (All WAN ports can be switched to LAN ports)
5G RU	Supported	Supported
Switch RU	Supported	Supported
WAC (Number of managed APs, Default/Maximum****)	32/1024	
SIC slot	4 x SIC	8 x SIC
WSIC slot (default/maximum****)	0/2	0/4
Console port	1 x RJ45 console port	1 x RJ45 console port
USB port	1 x USB3.0	1 x USB2.0
Memory (SPU)	16 GB	16 GB
Memory (MPU)		8 GB
TPM	Supported only by the NetEngine AR8140-T-12G10XG	Not supported

Specifications	NetEngine AR8140-12G10XG NetEngine AR8140-T-12G10XG	NetEngine AR8700-8
<p>*: Scenario where the SD-WAN IPsec performance specification applies: IPsec. This specification applies to the combined total of traffic in inbound and outbound directions.</p> <p>***: Scenario where the SD-WAN performance specification applies: IPsec + QoS. This specification applies to the combined total of traffic in inbound and outbound directions.</p> <p>***: Scenario where the typical SD-WAN performance specification applies: IPsec + QoS + SA + AppFlow. This specification applies to the combined total of traffic in inbound and outbound directions.</p> <p>****: By default, a maximum of 32 APs can be managed for free. If the number of APs exceeds the threshold, licenses must be purchased. NetEngine AR8000 series supports a maximum of 1024 APs.</p> <p>*****: The maximum number of slots includes the number of combined slots.</p>		
Dimensions and Weight		
Dimensions without packaging (excluding the parts protruding from the body) (H x W x D)	44.4 mm x 442.0 mm x 420.0 mm	88.1 mm x 442.0 mm x 482.8 mm
Dimensions without packaging (the depth is the distance from ports on the front panel to the handle on the rear panel) (H x W x D)	44.4 mm x 442.0 mm x 442.5 mm	88.1 mm x 442.0 mm x 525.1 mm
Dimensions with packaging (H x W x D)	185 mm x 550 mm x 650 mm	205 mm x 585 mm x 760 mm
Installation type	Rack	Rack
Chassis height	1 U	2 U
Power Specifications, Power Consumption, and Heat Dissipation		
Rated input voltage (V)	AC: 100 V to 240 V, 50 Hz/60 Hz HVDC: 240 V DC: -48 V/-60 V/+48 V	AC: 110 V/220 V, 50 Hz/60 Hz HVDC: 240 V DC: -48 V to -60 V NOTE: When the input voltage of an AC power module is 110 V, the AC power module cannot be used together with other power modules. If the AC power module is used together with other power modules, overcurrent protection may be triggered for the AC power module.
Input voltage range (V)	AC: 90 V to 290 V, 45 Hz to 65 Hz HVDC: 190 V to 290 V DC: -38.4 V to -72 V/+38.4 V to +57 V	AC: 90 V to 290 V; 45 Hz to 65 Hz HVDC: 190 V to 290 V DC: -38.4 V to -72 V
Maximum input current (A)	350 W AC: 5.5 A 350 W HVDC: 2.5 A 240 W DC: 8 A	600 W AC: 8 A (100 V to 130 V AC)/8 A (200 V to 240 V AC) 600 W HVDC: 4 A 1000 W AC: 12 A (100 V to 130 V AC)/8 A (200 V to 240 V AC) 1000 W HVDC: 8 A 1000 W DC: 30 A

Specifications	NetEngine AR8140-12G10XG NetEngine AR8140-T-12G10XG	NetEngine AR8700-8
Maximum output power (W)	350 W AC: 350 W 350 W HVDC: 350 W 240 W DC: 240 W	600 W AC: 300 W (100 V to 130 V AC)/600 W (200 V to 240 V AC) 600 W HVDC: 600 W 1000 W AC: 900 W (100 V to 130 V AC)/1000 W (200 V to 240 V AC) 1000 W HVDC: 1000 W 1000 W DC: 1000 W
Typical power consumption (W)	168 W	221 W (SPU + 2 x MPU + FAN)
Maximum power consumption (W)	191 W	288 W (SPU + 2 x MPU + FAN)
Power supply redundancy	Dual power supplies, hot-swappable	Dual power supplies, hot-swappable
Fan modules	Built-in unpluggable fan modules	Pluggable fan tray assembly
Airflow	Left-to-right	Left-to-rear + front-to-rear
Noise	57.6 dB(A)	57.6 dB(A)
Environment Parameters		
Operating temperature	0°C to 45°C	0°C to 45°C
Operating humidity	5% to 95% (non-condensing)	5% to 95% (non-condensing)
Operating altitude	< 5000 m	< 5000 m
Storage temperature	-40°C to +70°C	-40°C to +70°C

Software Features and Protocols

Item	NetEngine AR8000 Series
Basic function	DHCPv4 Server/Client/Relay, DHCPv6 Server/Client/Relay, PPPoE client, NAT, and sub-interface management, DNS
LAN	IEEE 802.1p, IEEE 802.1Q, VLAN management, VLAN aggregation, Voice VLAN, MAC management, STP/RSTP, MSTP
IPv4 unicast routing	Routing policies, static routes, RIP, OSPF, IS-IS, BGP, IP FRR
IPv6 unicast routing	Static routing, routing policies, RIPng, OSPFv3, IS-ISv6, BGP4+
Basic IPv6 function	ND, Path PMTU, IPv6 FIB, IPv6 ACL, ICMPv6, DNSv6, DHCPv6, PPPoE client IPv6, IPv4 over IPv6, IPv6 over IPv4
VPN	GRE, Ethernet over GRE, IPsec v4/v6, Segment Routing IPv6 (SRv6), L2TP client, DSVPN, IPv4/IPv6 dual-stack, SD-WAN EVPN
WAN optimization	A-FEC and data compression
Multicast	IGMP V1/V2/V3, PIM SM, PIM DM, MSDP, MBGP, IP multicast over SD-WAN
MPLS	MPLS LDP, MPLS L3VPN, Dynamic LSP, IP FRR, LDP FRR, MPLS 6VPE, MPLS 6PE
QoS	Priority mapping, traffic policing (CAR), traffic shaping, congestion avoidance, congestion management, MQC (traffic classifier, traffic behavior, and traffic policy), level-3 traffic scheduling and shaping (HQoS), application identification, intelligent policy-based routing (SPR), SaaS

Item	NetEngine AR8000 Series
	routing, Adaptive QoS, SaaS routing, Intelligent Traffic Policing(ITP)
Security	ACL/ACL6, firewall, AAA authentication, RADIUS, HWTACACS, NAC, PKI, broadcast storm suppression, ARP security, ICMP security, attack defense, URPF, CPCAR, attack source tracing, 802.1X authentication, portal authentication, port security, integrates NGFW capabilities, offering security policy control based on IP address (groups)/domain groups/applications/time ranges, ASPF, application recognition and control, IPS, URL filtering, Antivirus, signature database and antivirus database update, and interconnection with third-party SSE security clouds
System management	Upgrade management, device management, SNMP (v1/v2c/v3), RMON, NTP, USB-, DHCP option-, and email-based deployment, deployment through the registration query center, NETCONF/YANG/telemetry, TCP FPM, NQA, IFIT, NetStream/NetStream v6, switch RU plug-and-play, web-based management, LLDP for an RU, Event Versus Action(EVA)
WAC	<ul style="list-style-type: none"> •Management of Wi-Fi 5/6/7 Fit APs •CAPWAP protocol •WLAN user management •WLAN radio management •WLAN QoS •WLAN security •WLAN user roaming Supports 802.11k and 802.11v smart roaming, 802.11r fast roaming (≤ 50 ms) and AI roaming


Safety and Regulatory Standards

Item	NetEngine AR8000 Series
EMC standards compliance	<ul style="list-style-type: none"> •EN 55032 •EN 55035 •CISPR 32 •CISPR 35 •IEC/EN 61000-3-2 •EN 61000-3-3 •ETSI EN 300 386 •ETSI EN 301 489-1 •ETSI EN 301 489-3 •ETSI EN 301 489-17 •ETSI EN 301 489-52 •FCC CFR Part 15, Subpart B •ANSI C63.4 •ICES-003 Issue 7 •EN 50121-1 •EN 50121-4 •GB 9254
Environmental standards compliance	<ul style="list-style-type: none"> •RoHS •REACH •WEEE
Security standards	<ul style="list-style-type: none"> •IEC 60950-1

Item	NetEngine AR8000 Series
compliance	<ul style="list-style-type: none"> •IEC 62368-1 •EN 60950-1 •UL 60950-1 •CSA C22.2 No 60950-1 •GB 4943.1

Application Scenarios

SD-WAN networking



In the SD-WAN Solution, Huawei NetEngine AR8000 series routers can serve as gateways for enterprise headquarters or large branches and support multiple physical links such as MPLS private lines and Internet links. Additionally, they can be managed and visualized on iMaster NCE in a unified manner. The AR6710-H series provides extensive SD-WAN features such as intelligent application identification and intelligent traffic steering to deliver better service experience to enterprises. For details about Huawei SD-WAN Solution, visit

<https://e.huawei.com/en/solutions/enterprise-network/campus-network/branch-campus-network>.

Ordering Information

The configuration of the NetEngine AR8100 series includes device model selection and software configuration.

- Device model

Select the device model according to the uplink interface type and service requirements.

- Software

The NetEngine AR8100 series software consists of the basic software and licensed software. The basic software provides basic features such as routing, switching, and security, while the licensed software provides additional functions, such as security protection.

Host	Ordering Information
AR8140-12G10XG	AR8140-12G10XG, 10*10GE SFP+, 8*GE Combo, 4*GE electrical, 1*USB3.0, 4*SIC
AR8140-T-12G10XG	AR8140-T-12G10XG, 10*10GE SFP+, 8*GE Combo, 4*GE electrical, 1*USB3.0, 4*SIC

Software Sales Model	License	Ordering Information
Threat protection service	LAR0TP1201 LAR0TP1202 LAR0TP1203 LAR0TP1204 LAR0TP1205	Threat Protection Service Subscribe x Year (Applies to AR8100) (corresponding model: LAR0TP120x), including: <ul style="list-style-type: none"> • IPS signature database update • URL remote query for URL filtering • Antivirus signature database update
Independent Sale Model	AR81-LIC-Basic-IFIT	AR8100 Value-added Basic IFIT Package
	AR81-LIC-Enhance-IFIT	AR8100 Value-added Enhanced IFIT Package
	AR81-LIC-Enh-WANOP	AR8100 Value-added Enhanced WAN-Optimize Package, including: <ul style="list-style-type: none"> • Data Compression • Adaptive QoS
	AR81-LIC-NETCONN	AR8100 Value-added Network Connection Package, including: <ul style="list-style-type: none"> • DSVPN
N1 Model	N1-AR81-B	N1 AR8100 CloudCampus Basic Software (exclude SD-WAN), Per Device
	N1-AR81-F	N1 AR8100 CloudCampus Foundation (include SD-WAN), Per Device
	N1-AR81-A	N1 AR8100 CloudCampus Advanced (include SD-WAN), Per Device
	N1-AR81-E-IFIT	N1 AR8100 CloudCampus Add-On, Enhance IFIT, Per Device

The configuration of the NetEngine AR8700 series includes device model selection, MPU selection, and software configuration.

- Device model

Select the device model according to the uplink interface type and service requirements.

- MPU

Select a single or dual MPUs based on the actual service scenario.

- Software

The NetEngine AR8700 series software consists of the basic software and licensed software. The basic software provides basic features such as routing, switching, and security, while the licensed software provides additional functions, such as security protection.

Host	Ordering Information
NetEngine AR8700-8	AR8700-8 assembly chassis
SPU-700H	AR8700 Service Process Unit (SPU-700H), 1*40GE QSFP+, 8*10GE SFP+, 8*GE Combo
MPU-100	AR8700 Main Processing Unit (MPU-100)
MPU-100-T	AR8700 Main Processing Unit (MPU-100-T)

Software Sales Model	License	Ordering Information
Threat protection service	LAR0TP1501 LAR0TP1502 LAR0TP1503 LAR0TP1504 LAR0TP1505	Threat Protection Service Subscribe x Year (Applies to AR8700) (corresponding model: LAR0TP150x), including: <ul style="list-style-type: none"> • IPS signature database update • URL remote query for URL filtering • Antivirus signature database update
Independent Sale Model	AR87-LIC-Basic-IFIT	AR8700 Value-added Basic IFIT Package
	AR87-LIC-Enhance-IFIT	AR8700 Value-added Enhanced IFIT Package
	AR87-LIC-Enh-WANOP	AR8700 Value-added Enhanced WAN-Optimize Package, including: <ul style="list-style-type: none"> • Data Compression • Adaptive QoS
	AR87-LIC-NETCONN	AR8700 Value-added Network Connection Package, including: <ul style="list-style-type: none"> • DSVPN
N1 Model	N1-AR87-B	N1 AR8700 CloudCampus Basic Software (exclude SD-WAN), Per Device
	N1-AR87-F	N1 AR8700 CloudCampus Foundation (include SD-WAN), Per Device
	N1-AR87-A	N1 AR8700 CloudCampus Advanced (include SD-WAN), Per Device
	N1-AR87-E-IFIT	N1 AR8700 CloudCampus Add-On, Enhance IFIT, Per Device

Other Information

SIC Port Model	Ordering Information
SIC-4E1-V2	4-Port Channelized E1 Interface Card
SIC-4GET-V2	4-Port GE LAN/WAN Interface Card
SIC-4STM1-V2	4-Port 155M Packet over SDH/Sonet Optical Interface Card
SIC-NRGL-V2	5G NR/LTE Interface Card
1V35B-V2*	4-Port VDSL2 WAN Interface Card

* : Only PTM mode is supported.

WSIC Port Model	Ordering Information
WSIC-4GE-C-V2	4-Port GE COMBO LAN/WAN Interface Card
5G RU	Frequency Band
RU-201	<ul style="list-style-type: none"> •5G: NR Band 1/3/5/7/8/20/28/38/40/41/75/77/78/79/80/81/82/83/84 •LTE: Band 1/3/5/7/8/18/19/20/26/28/32/34/38/39/40/41/42/43 •DL MIMO: <ul style="list-style-type: none"> 5G 4x4: NR Band 1/3/7/38/40/41/77/78/79 5G 2x2: NR Band 5/8/20/28/75 LTE 4x4: Band 1/3/7/38/39/40/41/42/43 LTE 2x2: Band 5/8/18/19/20/26/28/32/34 •UL MIMO: <ul style="list-style-type: none"> 5G 2x2: NR Band1/38/40/41/77/78/79
Switch RU	Model
Switch RU	CloudEngine S5731-L series, CloudEngine S5731S-L series, CloudEngine S5731I-L series, CloudEngine S5751-L series

More Information


For more information, visit <https://e.huawei.com/en/> or contact us in the following ways:

- Global service hotline: <http://e.huawei.com/en/service-hotline>
- Logging in to the Huawei Enterprise technical support website: <http://support.huawei.com/enterprise/>
- Sending an email to the customer service mailbox: support_e@huawei.com

Copyright © Huawei Technologies Co., Ltd. 2021. All rights reserved.

No part of this document may be reproduced or transmitted in any form or by any means without prior written consent of Huawei Technologies Co., Ltd.

Trademarks and Permissions

 HUAWEI and other Huawei trademarks are trademarks of Huawei Technologies Co., Ltd.

All other trademarks and trade names mentioned in this document are the property of their respective holders.

Notice

The purchased products, services and features are stipulated by the contract made between Huawei and the customer. All or part of the products, services and features described in this document may not be within the purchase scope or the usage scope. Unless otherwise specified in the contract, all statements, information, and recommendations in this document are provided "AS IS" without warranties, guarantees or representations of any kind, either express or implied.

The information in this document is subject to change without notice. Every effort has been made in the preparation of this document to ensure accuracy of the contents, but all statements, information, and recommendations in this document do not constitute a warranty of any kind, express or implied.

Huawei Technologies Co., Ltd.

Address: Huawei Industrial Base
Bantian, Longgang Shenzhen 518129
People's Republic of China
Website: www.huawei.com