

# Lenovo ThinkSystem DE4800H and DE4800F Storage Arrays

## Product Guide

Lenovo ThinkSystem DE4800H and DE4800F are a new generation of hybrid and all flash mid-range storage systems that are designed to provide high performance, simplicity, capacity, security, scalable, and high availability for medium to large businesses. The ThinkSystem DE4800H and DE4800F deliver enterprise-class storage management capabilities in a performance-optimized system with a wide IO flexibility of host connectivity options, flexible drive configurations, and enhanced data management features. The ThinkSystem DE4800H and DE4800F are a perfect fit for a wide range of enterprise workloads, including big data and analytics, video surveillance, technical computing, backup and recovery, and other storage I/O-intensive applications.

The Lenovo ThinkSystem DE4800H 2U24 enclosure is shown in the following figure.



Figure 1. Lenovo ThinkSystem DE4800H 2U24 enclosure

[3D Tour for DE Hybrid](#)
[3D Tour for DE All Flash](#)

### Did you know?

Lenovo ThinkSystem DE4800H and DE4800F are well positioned for those customers looking for enhancements in the following areas.

**Increased Bandwidth:** "Multiple ports allow for higher aggregate data transfer rates" and "Reducing the risk of bottlenecks and improving overall system performance".

**Efficient Caching:** "Faster memory speed to maximize performance" and "More memory enables more effective caching strategies, where frequently accessed data is kept in fast-access memory, thus speeding up data retrieval times".

**Networking flexibility:** "Optimize for various workloads and performance requirements by mixing multiple connectivity types (e.g., Fibre Channel, iSCSI)".

## Key features

The Lenovo ThinkSystem DE4800H scales up to 300 HDD or 120 SSDs.

The Lenovo ThinkSystem DE4800F scales up to 120 SSDs.

The ThinkSystem DE4800H and DE4800F offer the following key features and benefits:

- Scalable, high performance mid-range hybrid storage with dual active/active controller configurations with 32 GB or 64 GB system memory per controller for high availability and performance.
- Improved performance and data protection with Dynamic Disk Pools (DDP) technology, as well as support for traditional RAID 0, 1, 3, 5, 6, and 10.
- Flexible storage protocols to match diverse client needs with support for 12 Gb SAS, 10/25 Gb iSCSI, or 16/32 Gb FC host connectivity.
- 12 Gb SAS drive-side connectivity with support for up to 24x 2.5-inch small form factor (SFF) drives in the 2U24 SFF enclosures, up to 12x 3.5-inch large form factor (LFF) drives in the 2U12 LFF enclosures, or up to 60x 3.5-inch LFF drives in the 4U60 LFF enclosures. See the [Drives](#) section for details.
- Base scalability with the optional upgrade to increase the number of drives by attaching ThinkSystem DE240S 2U24 SFF, DE120S 2U12 LFF, and DE600S 4U60 LFF expansion enclosures to satisfy growing needs for storage capacity and performance.
- Rich set of standard storage management functions available at no extra cost, including Dynamic Disk Pools, SSD read cache, snapshots, volume copy, thin provisioning, and encryption (requires optional FIPS drives).
- Snapshots for greater scalability and synchronous or asynchronous mirroring for continuous data availability.
- Intuitive, web-based GUI for easy system setup and management.
- Designed for 99.9999% availability with redundant hot-swap components, including controllers and I/O modules, power supplies, cooling modules (4U60 LFF enclosures only), proactive maintenance, and non-disruptive firmware upgrades.

The ThinkSystem DE4800H and DE4800F support the complete range of data storage requirements, from highly used applications to high-capacity, low usage applications.

The ThinkSystem DE4800H and DE4800F offer high levels of system and data availability with the following technologies:

- Dual-active controller modules with automatic load balancing and failover
- Mirrored data cache with flash backup (battery-backed destaging to flash)
- Dual-port SAS HDDs and SSDs with automatic drive failure detection and rebuild with global hot spares
- Redundant, hot-swappable and customer replaceable hardware components, including SFP/SFP+ transceivers, controller and I/O modules, power supplies, cooling modules (4U60 LFF only), and drives
- Automated path failover support for the data path between the host and the drives with multipathing software
- Non-disruptive controller and drive firmware upgrades

## Components and connectors

The following figure shows the front of the Lenovo ThinkSystem DE4800H 2U12 LFF enclosure.




Figure 2. ThinkSystem DE4800H 2U12 LFF enclosure front view

The following figure shows the front of the ThinkSystem DE4800H 2U24 SFF enclosure.




Figure 3. ThinkSystem DE4800H 2U24 SFF enclosure front view

The following figure shows the front of the ThinkSystem DE4800H 4U60 LFF enclosure.




Figure 4. ThinkSystem DE4800H 4U60 LFF enclosure front view

The following figure shows the rear of the ThinkSystem DE4800H and DE4800F enclosure.




Figure 5. ThinkSystem DE4800H and DE4800F enclosure rear view

Each DE4800H / DE4800F controller includes the following components:

- Two redundant hot-swap controllers, **each controller** with the following ports:
  - One slot for the host interface card (a host interface card is required)
    - Note:** The DE4800H and DE4800F controllers support base ports
      - Lenovo ThinkSystem DE4200/DE4800 32Gb FC,4-ports
      - Lenovo ThinkSystem DE4200/DE4800 10Gb Base-T iSCSI 4-ports
      - Lenovo ThinkSystem DE4200/DE4800 12Gb SAS 4-ports
  - Two 12 Gb SAS x4 expansion ports (Mini-SAS HD SFF-8644) for connections to the expansion enclosures.
    - Note:** The 12 Gb SAS x4 expansion port next to two expansion ports is not available for use.
  - One RJ-45 10/100/1000 Mb Ethernet port for out-of-band management.
  - One serial console ports (RJ-45 and USB-C) for another means to configure the system.
  - One USB-C host management port
  - One USB service port (not enable/ inactive)
  - Two onboard 10/25 Gb iSCSI for host connection
- Two redundant hot-swap 913 W AC (100 - 240 V) power supplies (IEC 320-C14 power connector) with integrated cooling fans.

The following figure shows the rear of the ThinkSystem DE240S and DE120S 2U expansion enclosures.




Figure 6. ThinkSystem DE240S and DE120S 2U expansion enclosures rear view

The rear of the ThinkSystem DE240S and DE120S 2U expansion enclosures includes the following components:

- Two redundant hot-swap I/O Modules; each I/O Module provides four 12 Gb SAS x4 expansion ports (Mini-SAS HD SFF-8644) for connections to the controller enclosures and for connecting the expansion enclosures between each other.
- Two redundant hot-swap 913 W AC (100 - 240 V) power supplies (IEC 320-C14 power connector) with integrated cooling fans.

The following figure shows the front of the ThinkSystem DE4800H and DE600S 4U LFF enclosures without the front bezel.




Figure 7. ThinkSystem DE4800H 4U60 and DE600S 4U LFF enclosures front view (without the front bezel)

The front of the ThinkSystem DE4800H 4U60 and DE600S 4U LFF enclosures includes the following components:

- Five drawers, each with 12 LFF hot-swap drive bays
- Enclosure status LEDs
- Enclosure ID LED

The following figure shows the rear of the ThinkSystem DE4800H 4U60 LFF controller enclosure.




Figure 8. ThinkSystem DE4800H 4U60 LFF enclosure rear view

The rear of the ThinkSystem DE4800H 4U60 LFF controller includes the following components:

- Two redundant hot-swap controllers, **each controller** with the following ports:
  - One slot for the host interface card (a host interface card is required)
    - Note:** The DE4800H and DE4800F controllers support base ports
      - Lenovo ThinkSystem DE4200/DE4800 32Gb FC,4-ports
      - Lenovo ThinkSystem DE4200/DE4800 10Gb Base-T iSCSI 4-ports
      - Lenovo ThinkSystem DE4200/DE4800 12Gb SAS 4-ports
  - Two 12 Gb SAS x4 expansion ports (Mini-SAS HD SFF-8644) for connections to the expansion enclosures.
    - Note:** The 12 Gb SAS x4 expansion port next to two expansion ports is not available for use.
  - One RJ-45 10/100/1000 Mb Ethernet port for out-of-band management.
  - One serial console ports (RJ-45 and USB-C) for another means to configure the system.
  - One USB-C Host management port
  - One USB service port (not enable/ inactive)
  - Two onboard 10/25 Gb iSCSI for host connection
- Two redundant hot-swap 2325 W AC (200 - 240 V) power supplies (IEC 320-C20 power connector)
- Two hot-swap cooling fan modules; each module has two fans.
  - Note:** The failed cooling module should be replaced as soon as possible.



The following figure shows the rear of the ThinkSystem DE600S 4U LFF expansion enclosure.




Figure 9. ThinkSystem DE600S 4U LFF expansion enclosure rear view

The rear of the ThinkSystem DE600S 4U LFF expansion enclosure includes the following components:

- Two redundant hot-swap I/O Modules; each I/O Module provides four 12 Gb SAS x4 expansion ports (Mini-SAS HD SFF-8644) for connections to the controller enclosures and for connecting the expansion enclosures between each other.
- Two redundant hot-swap 2325 W AC (200 - 240 V) power supplies (IEC 320-C20 power connector)
- Two hot-swap cooling fan modules; each module has two fans.  
**Note:** The failed cooling module should be replaced as soon as possible.



## System specifications

The following table lists the Lenovo ThinkSystem DE4800H and DE4800F storage system specifications.

**Note:** The supported hardware options, software features, and interoperability listed in this product guide are based on the software version 11.60. For details about specific software releases that introduced support for certain hardware options and software features, refer to the Release notes of the particular software release for the ThinkSystem Lenovo ThinkSystem DE4800H and DE4800F that can be found at:

<http://datacentersupport.lenovo.com>

Table 1. ThinkSystem DE4800H and DE4800F systems specifications

Attribute	Specification
Form factor	<ul style="list-style-type: none"> <li>Lenovo ThinkSystem DE4800H Hybrid SAS 2U12 (Machine Type 7DCB): 2U rack mount.</li> <li>Lenovo ThinkSystem DE4800H Hybrid SAS 2U24 (Machine Type 7DCR): 2U rack mount</li> <li>Lenovo ThinkSystem DE4800H Hybrid SAS 4U60 (Machine Type 7DCS): 4U rack mount</li> <li>Lenovo ThinkSystem DE4800F All Flash SAS 2U24 (Machine Type 7DCC): 2U rack mount</li> <li>DE120S 2U12 LFF expansion enclosure (Machine Type 7Y63): 2U rack mount</li> <li>DE240S 2U24 SFF expansion enclosure (Machine Type 7Y68): 2U rack mount.</li> <li>DE600S 4U60 LFF expansion enclosure (Machine Type 7Y69): 4U rack mount.</li> </ul>
Controller configuration	Dual active-active controller configuration with automatic load balancing.
RAID levels	RAID 0, 1, 3, 5, 6, and 10; Dynamic Disk Pools. <b>Note:</b> RAID 3 can be configured only through the CLI.
Controller system memory	DE4800H: 64 GB or 128 GB per system (32 GB or 64 GB per controller).  DE4800F: 128G per system (64 GB per controller).  Cache mirroring between the controllers. Flash-backed cache protection (includes battery for destaging to flash).
Expansion enclosure support	DE4800H storage system: <ul style="list-style-type: none"> <li>DE4800H 2U12 SFF controller: 7x DE120S, 7x DE240S or 4x DE600S</li> <li>DE4800H 2U24 SFF controller: 7x DE120S, 7x DE240S or 4x DE600S</li> <li>DE4800H 4U60 LFF controller: 7x DE120S, 7x DE240S or 4x DE600S               <ul style="list-style-type: none"> <li>Expansion enclosures may be mixed (intermix) up to a maximum of 7 expansion enclosures</li> </ul> </li> </ul> DE4800F storage system: <ul style="list-style-type: none"> <li>DE4800F 2U24 SFF controller: 4x DE240S</li> </ul>

Attribute	Specification
Drive bays	<p>DE4800H storage system:</p> <ul style="list-style-type: none"> <li>Model 1: DE4800H 2U12 LFF (7DCB) <ul style="list-style-type: none"> <li>12 LFF drive bays in the the main (base) unit enclosure</li> </ul> </li> <li>Model 2: DE4800H Hybrid SAS 2U24 (7DCR) <ul style="list-style-type: none"> <li>24 SFF drive bays in the the main (base) unit enclosure</li> </ul> </li> <li>Model 3: DE4800H Hybrid SAS 4U60 (7DCS) <ul style="list-style-type: none"> <li>60 LFF drive bays in the the main (base) unit enclosure</li> </ul> </li> <li>Expansion enclosures supported: 2U12 LFF, 2U24 SFF, 4U60 LFF</li> </ul> <p>DE4800F storage system:</p> <ul style="list-style-type: none"> <li>Model 1: DE4800F All Flash SAS 2U24 (7DCC) <ul style="list-style-type: none"> <li>24 SFF drives in the main (base) unit enclosure</li> </ul> </li> <li>Expansion enclosure supported: 2U24 SFF</li> </ul> <p>See <a href="#">Drives specifications</a> for details.</p>
Drive technology	<ul style="list-style-type: none"> <li>12 Gb SAS and NL SAS HDDs and FIPS HDDs, 12 Gb SAS SSDs and FIPS SSDs.</li> <li>Intermix of HDDs and SSDs is supported within a system.</li> <li>Intermix of HDDs and SSDs is <i>not</i> supported within a volume group or disk pool.</li> <li>Intermix of FIPS drives and non-FIPS drives is supported within a system.</li> <li>Intermix of FIPS drives and non-FIPS drives is <i>not</i> supported within a volume group or disk pool.</li> </ul>
Drive expansion connectivity	<ul style="list-style-type: none"> <li>On board, per controller: 2x 12 Gb SAS x4 (Mini-SAS HD SFF-8644) expansion ports for the attachment to expansion enclosures.</li> <li>On board, for enclosure: 4x 12 Gb SAS x4 (Mini-SAS HD SFF-8644) expansion ports for the attachment to expansion enclosures.</li> </ul>
Drives	<p>2U24 SFF drives:</p> <ul style="list-style-type: none"> <li>10K rpm SAS HDDs</li> <li>10K rpm SAS FIPS HDDs</li> <li>SAS SSDs (1 DWD)</li> </ul> <p>2U12 LFF drives:</p> <ul style="list-style-type: none"> <li>7.2K rpm SAS HDDs</li> <li>7.2K rpm SAS FIPS HDDs</li> </ul> <p>4U60 LFF drives:</p> <ul style="list-style-type: none"> <li>7.2K rpm SAS HDDs</li> <li>7.2K rpm SAS FIPS HDDs</li> <li>SAS SSDs (1 DWD)</li> </ul>
Storage capacity	<ul style="list-style-type: none"> <li>Base configuration (DE4800H 4U60 + 4x DE600S enclosures): 7.2 PB (300x 24 TB SAS HDDs).</li> <li>Base configuration (DE4800F 2U24 + 4x DE240S enclosures): 1.84 PB (120x 15.36 TB SSDs).</li> </ul>
Storage protocols	SAN (Block access): SAS, iSCSI, FC.

Attribute	Specification
Host connectivity	<p>Base ports (enclosure with two controllers):</p> <ul style="list-style-type: none"> <li>4x 10/25 Gb iSCSI (DAC or SW fiber optics, LC)</li> </ul> <p><b>Note:</b> 25 Gbps transceivers are not auto-negotiating down to 10 Gbps</p> <p>Host connectivity ports provided using host interface cards (HICs). Listed below are ports per enclosure. Enclosure supports two controllers:</p> <ul style="list-style-type: none"> <li>8x 12 Gb SAS host ports (Mini-SAS HD, SFF-8644) (4 ports per controller)</li> <li>8x 10 Gb BaseT host ports (RJ45 Cat5/6 copper cables) (4 ports per controller)</li> <li>8x 16/32 Gb FC SFP+ host ports (SW fiber optics, LC) (4 ports per controller)</li> </ul> <p><b>Note:</b> There are base ports (onboard 10/25 Gb iSCSI) available. A configuration with base ports only and no HICs is supported. Or leveraging both or either for host connectivity are supported.</p>
Host operating systems	<p>Microsoft Windows Server; Red Hat Enterprise Linux (RHEL); SUSE Linux Enterprise Server (SLES); VMware vSphere.</p> <p><b>Note:</b> Reference <a href="#">LSIC</a> for specific Operating System details.</p>
Standard software features	Dynamic Disk Pools, SSD read cache, snapshots (up to 512 snapshots max), volume copy, thin provisioning (DDP only), encryption (requires optional FIPS drives), and data assurance.
Optional software features	Snapshots (up to 512 max), synchronous mirroring, and asynchronous mirroring.
Performance*	<ul style="list-style-type: none"> <li>Up to 900 000 random read IOPS (4 KB blocks)</li> <li>Up to 135 000 random write IOPS (4 KB blocks)</li> <li>Sequential read throughput up to 12 GBps</li> <li>Sequential write throughput up to 9.4 GBps</li> <li>Full Stripe Write Acceleration (FSWA) up to 10.8 GBps</li> </ul>
Configuration maximums**	<ul style="list-style-type: none"> <li>Maximum storage capacity: 3.84 PB (base) / 7.2 PB</li> <li>Maximum number of logical volumes: 2048</li> <li>Maximum logical volume size: 4 PB</li> <li>Maximum thin-provisioned logical volume size (DDP only): 256 TB</li> <li>Maximum number of drives in a RAID volume group: <ul style="list-style-type: none"> <li>RAID 0, 1/10: 240 (base) / 300</li> <li>RAID 3, 5, 6: 30</li> </ul> </li> <li>Maximum number of DDP arrays: 20</li> <li>Maximum number of drives; 300</li> <li>Maximum SSD read cache size: 5 TB</li> <li>Maximum number of hosts: 512</li> <li>Maximum number of snapshots: base: 256 and 512 optional FoD upgrade</li> <li>Maximum number of mirroring pairs: 128 (requires an optional license)</li> </ul>
Cooling	Redundant cooling with two cooling modules (4U60 LFF) or with the fans that are built into power supplies (2U24 SFF).
Power supply	Two redundant hot-swap 913 W (100 - 240 V) (2U24 enclosures) or 2325 W (200 - 240 V) (4U60 enclosures) Platinum AC power supplies.
Hot-swap parts	Controllers, I/O modules, drives, power supplies, cooling modules (4U60 LFF only), and SFP+/SFP28 transceivers.
Management ports	<ul style="list-style-type: none"> <li>1x 1 GbE port (UTP, RJ-45) per controller for out-of-band management.</li> <li>2x Serial console ports (RJ-45 and USB-C) for system configuration.</li> <li>In-band management via I/O path.</li> </ul>
Management interfaces	System Manager web-based GUI; SAN Manager standalone GUI; Serial console CLI, SNMP, email, and syslog alerts; optional Lenovo XClarity.
Security features	Secure Socket Layer (SSL), user level security, role-based access control (RBAC), LDAP authentication.

Attribute	Specification		
Warranty and support	Three-year customer-replaceable unit and onsite limited warranty with 9x5 next business day (NBD) parts delivered. Also available are 9x5 NBD onsite response, 24x7 coverage with 2-hour or 4-hour onsite response, or 6-hour or 24-hour committed repair (select areas), YourDrive YourData, Premier Support, and 1-year or 2-year post-warranty extensions.		
Software maintenance	Included in the base warranty and any Lenovo warranty extensions.		
Dimensions	2U24 SFF enclosure: <ul style="list-style-type: none"> <li>● Height: 85 mm (3.4 in.)</li> <li>● Width: 449 mm (17.7 in.)</li> <li>● Depth: 553 mm (21.8 in.)</li> </ul>	2U12 LFF enclosure: <ul style="list-style-type: none"> <li>● Height: 85 mm (3.4 in.)</li> <li>● Width: 447 mm (17.6 in.)</li> <li>● Depth: 483 mm (19.0 in.)</li> </ul>	4U60 LFF enclosure: <ul style="list-style-type: none"> <li>● Height: 174 mm (6.9 in.)</li> <li>● Width: 449 mm (17.7 in.)</li> <li>● Depth: 922 mm (36.3 in.)</li> </ul>
Weight	<ul style="list-style-type: none"> <li>● DE4800H 2U12 LFF controller enclosure (7DCB): 25.07 kg (55.3 lb)</li> <li>● DE4800H 2U24 SFF controller enclosure (7DCR): 25.07 kg (55.3 lb)</li> <li>● DE4800H 4U60 LFF controller enclosure (7DCS): 108.49 kg (239.2 lb)</li> <li>● DE4800F 2U24 SFF controller enclosure (7DCC): 25.07 kg (55.3 lb)</li> <li>● DE120S 2U12 LFF expansion enclosure (7Y63): 27.12 kg (59.8 lb)</li> <li>● DE240S 2U24 SFF expansion enclosure (7Y68): 27.44 kg (60.5 lb)</li> <li>● DE600S 4U60 LFF expansion enclosure (7Y69): 112.2 kg (247.4 lb)</li> </ul>		

\* Estimated performance based on internal measurements.

\*\* For more specific configuration performance please use Lenovo sizing tool or contact Lenovo representative:

<https://storagesizing.tools.lenovo.com/>

## Controller enclosures

ThinkSystem DE4800H controller enclosure models are available in a 2U or 4U rack mount.

- DE4800H Hybrid SAS 2U12
- DE4800H Hybrid SAS 2U24
- Hybrid SAS 4U60
  - DE4800H models include two controllers, each with 32 GB or 64 GB system memory for a system total of 64 GB or 128 GB.
  - Base ports 10/25 Gb iSCSI, optional for host connectivity 16/32 Gb Fibre Channel (FC), 10 Gb BaseT and 12 Gb SAS.

ThinkSystem DE4800F controller enclosure model is available in a 2U rack mount.

- All Flash SAS 2U24
  - DE4800F model includes two controllers each with 64 GB system memory for a system total of 128 GB.
  - Base ports 10/25 Gb iSCSI, optional for host connectivity 16/32 Gb Fibre Channel (FC), 10 Gb BaseT and 12 Gb SAS.

The following table lists the CTO base models for the Lenovo ThinkSystem DE4800H and DE4800F.

Table 2. Lenovo ThinkSystem DE4800H and DE4800F CTO base models

Machine Type/Model	Base feature	Description
7DCBCTO1WW	BEY6	Lenovo ThinkSystem DE4800H Hybrid SAS 2U12
7DCRCTO1WW	BEY7	Lenovo ThinkSystem DE4800H Hybrid SAS 2U24
7DCSCTO1WW	BQ9W	Lenovo ThinkSystem DE4800H Hybrid SAS 4U60
7DCCCTO1WW	BEY7	Lenovo ThinkSystem DE4800F All Flash SAS 2U24

The models of the ThinkSystem DE4800H ship with the following items:

- One chassis with the following components:
  - Two controllers
  - Two power supplies
  - Two cooling modules (4U60 LFF only)
  - Two host interface cards
- Rack Mount Kit
- 2 m USB Cable (USB Type A to USB-C)
- Quick Installation Guide
- Electronic Publications Flyer
- CTO models: Customer-configured power cables

The following table lists the specifications for the ThinkSystem DE4800H and DE4800F

Table 3. Controller enclosure specifications

Product Name	DE4800H LFF (7DCB)	DE4800H SFF (7DCR)	DE4800H LFF (7DCS)	DE4800F SFF (7DCC)
Controller (per system)	2	2	2	2
Standard cache (per system)	64 GB	64 GB	64 GB	128 GB
Maximum cache (per system)	128 GB	128 GB	128 GB	128 GB
Standard Host port type	32Gb FC	32Gb FC	32Gb FC	32Gb FC
Standard Host Port Quantity (per system)	12	12	12	12
Optional Host Ports(must select one)	N/A*	N/A*	N/A*	N/A*
12 Gb SAS (Port quantity per system)	8	8	8	8
8 Gb FC (Port quantity per system)	0	0	0	0
16 Gb FC (Port quantity per system)	0	0	0	0
32 Gb FC (Port quantity per system)	8	8	8	8
10 Gb Ethernet Cu (iSCSI) (Port quantity per system)	8 **	8 **	8 **	8 **
10 Gb Ethernet (iSCSI) (Port quantity per system)	4***	4***	4***	4***
25Gb Ethernet (iSCSI) (Port quantity per system)	4***	4***	4***	4***
100Gb Ethernet (RoCE) (Port quantity per system)	0	0	0	0
Management Port Type	RJ45	RJ45	RJ45	RJ45
Management Port Quantity	2	2	2	2
Expansion Port Type	x4 SAS	x4 SAS	x4 SAS	x4 SAS
Standard Expansion Port Quantity (per system)	4	4	4	4
Maximum expansion enclosures per control enclosure	7, 7, 4	7, 7, 4	7, 7, 4	4
Supported Expansion Enclosures	7Y63, 7Y68, 7Y69	7Y63, 7Y68, 7Y69	7Y63, 7Y68, 7Y69	7Y68

\* iSCSI only

\*\* 10Gb Base-T iSCSI 4 ports HIC

\*\*\* 4 onboard ports can be either 10G or 25G

## Controllers

The Lenovo ThinkSystem DE4800H enclosures ship with two DE4800 controllers, and each controller provides 32 GB or 64 GB system memory for a system total of 64 GB or 128 GB, respectively.

The Lenovo ThinkSystem DE4800F enclosures ship with two DE4800 controllers, and each controller provides 64 GB system memory for a system total of 128 GB, respectively.

A controller provides interfaces for host connectivity, management, and internal drives, and it runs storage management software.

The ThinkSystem DE4800H and DE4800F controllers ship with two universal ports (two ports per controller) for 10 / 25 Gb iSCSI host connectivity.

Each controller has one expansion slot for a host interface card (HIC).

The following host interfaces can be added to the ThinkSystem DE4800 controller enclosures with HICs:

- 8x 12 Gb SAS x4 (Mini-SAS HD SFF-8644) ports (4 ports per HIC) for SAS connectivity.
- 8x 16/32 Gb FC SFP+ ports (4 ports per HIC) for FC connectivity (require optical transceivers that should be purchased for the HICs).
- 8x 10 Gb BaseT iSCSI ports (4 ports per HIC) for connectivity (require RJ-45 Cat5/6 cables).

Each DE4800 controller also provide two 12 Gb SAS x4 expansion ports (Mini-SAS HD SFF-8644 connectors) for the attachment of the ThinkSystem DE Series expansion units.

**Configuration notes:**

- Both controllers must have the same system memory: 32 GB or 64 GB.
- Two host interface cards are required for selection (one per controller).
- All base ports in the system require optical transceivers and or DAC cables.
- Both controllers must have the same type of the host interface card installed (12 Gb SAS SFF-8644, 32 Gb FC SFP+, 1/10 Gb BaseT iSCSI (copper RJ-45)).

The following table lists the DE4800 controllers and supported connectivity options.

Table 4. DE48000 controllers and connectivity options

Part number	Feature code	Description	Maximum quantity per controller enclosure
<b>Controllers</b>			
None*	C3HZ	Lenovo ThinkSystem DE4800 Controller 32G	2
None*	C3HY	Lenovo ThinkSystem DE4800 Controller 64G	2
<b>Host interface cards</b>			
4C57A95287	BWTF	Lenovo ThinkSystem DM3010/DE4200/DE4800 HIC, 16/32Gb FC,4-Ports	2
4C57A95288	BWTH	Lenovo ThinkSystem DM3010/DE4200/DE4800 HIC, 10GbBaseT, 4-Ports	2
4XC7A87081	C3HQ	Lenovo ThinkSystem DE4200/4800 HIC, 12Gb SAS,4-Ports	2
<b>Transceiver options</b>			
4M17A13529	B4B4	Lenovo 10/25GbE iSCSI SFP28 Module	4
4M17A13528	B4B3	Lenovo 32Gb FC SFP+ Transceiver	8
<b>OM4 cables for 16/32 Gb FC and 10/25 Gb iSCSI SW SFP+/SFP28 optical transceivers</b>			
4Z57A10845	B2P9	Lenovo 0.5m LC-LC OM4 MMF Cable	12
4Z57A10846	B2PA	Lenovo 1m LC-LC OM4 MMF Cable	12
4Z57A10847	B2PB	Lenovo 3m LC-LC OM4 MMF Cable	12
4Z57A10848	B2PC	Lenovo 5m LC-LC OM4 MMF Cable	12
4Z57A10849	B2PD	Lenovo 10m LC-LC OM4 MMF Cable	12
4Z57A10850	B2PE	Lenovo 15m LC-LC OM4 MMF Cable	12
4Z57A10851	B2PF	Lenovo 25m LC-LC OM4 MMF Cable	12
4Z57A10852	B2PG	Lenovo 30m LC-LC OM4 MMF Cable	12
<b>OM3 cables for 16/32 Gb FC and 10/25 Gb iSCSI SW SFP+/SFP28 optical transceivers</b>			
00MN499	ASR5	Lenovo 0.5m LC-LC OM3 MMF Cable	12
00MN502	ASR6	Lenovo 1m LC-LC OM3 MMF Cable	12
00MN505	ASR7	Lenovo 3m LC-LC OM3 MMF Cable	12
00MN508	ASR8	Lenovo 5m LC-LC OM3 MMF Cable	12
00MN511	ASR9	Lenovo 10m LC-LC OM3 MMF Cable	12



Part number	Feature code	Description	Maximum quantity per controller enclosure
00MN514	ASRA	Lenovo 15m LC-LC OM3 MMF Cable	12
00MN517	ASRB	Lenovo 25m LC-LC OM3 MMF Cable	12
00MN520	ASRC	Lenovo 30m LC-LC OM3 MMF Cable	12
DAC cables for 10 Gb iSCSI SFP+ base ports and iSCSI HIC ports			
00D6288	A3RG	0.5m Passive DAC SFP+ Cable	12
90Y9427	A1PH	1m Passive DAC SFP+ Cable	12
00AY764	A51N	1.5m Passive DAC SFP+ Cable	12
00AY765	A51P	2m Passive DAC SFP+ Cable	12
90Y9430	A1PJ	3m Passive DAC SFP+ Cable	12
90Y9433	A1PK	5m Passive DAC SFP+ Cable	12
00D6151	A3RH	7m Passive DAC SFP+ Cable	12
DAC cables for 25 Gb iSCSI SFP28 HIC ports			
7Z57A03557	AV1W	Lenovo 1m Passive 25G SFP28 DAC Cable	4
7Z57A03558	AV1X	Lenovo 3m Passive 25G SFP28 DAC Cable	4
SAS host connectivity cables: Mini-SAS HD (controller) to Mini-SAS HD (host)			
00YL847	AU16	External MiniSAS HD 8644/MiniSAS HD 8644 0.5M Cable	8
00YL848	AU17	External MiniSAS HD 8644/MiniSAS HD 8644 1M Cable	8
00YL849	AU18	External MiniSAS HD 8644/MiniSAS HD 8644 2M Cable	8
00YL850	AU19	External MiniSAS HD 8644/MiniSAS HD 8644 3M Cable	8
1 GbE management ports			
00WE123	AVFW	0.75m Green Cat6 Cable	10
00WE127	AVFX	1.0m Green Cat6 Cable	10
00WE131	AVFY	1.25m Green Cat6 Cable	10
00WE135	AVFZ	1.5m Green Cat6 Cable	10
00WE139	AVG0	3m Green Cat6 Cable	10
90Y3718	A1MT	10m Green Cat6 Cable	10
90Y3727	A1MW	25m Green Cat6 Cable	10

\* Factory-installed only.

## Expansion enclosures

In the base configuration, the ThinkSystem DE4800H supports attachment of up to seven ThinkSystem DE240S 2U24 SFF or ThinkSystem DE120S 2U12 LFF, or up to four ThinkSystem DE600S 4U60 LFF, or a combination of the DE240S 2U24 SFF, DE120S 2U12 LFF, and DE600S 4U60 LFF expansion enclosures for a total of up to 300 drives per system.

In the base configuration, the ThinkSystem DE4800F supports attachment of up to four ThinkSystem DE240S 2U24 SFF for a total of up to 120 drives per system.

Intermix of 2U24 SFF, 2U12 LFF, and 4U60 LFF expansion enclosures behind a 2U24 SFF or 4U60 LFF controller enclosure is supported up to the maximum number of enclosures and drives supported per system. The expansion enclosures can be added to the system non-disruptively.

The following table lists the CTO base models for the ThinkSystem DE Series expansion enclosures.

Table 5. ThinkSystem DE240S, DE120S, and DE600S CTO base models

Description	Machine Type/Model	Feature code		
		European Union	Other markets	World Wide
Lenovo ThinkSystem Storage 2U24 Chassis (with 2x PSUs)	7Y68CTO1WW*	BEY7	B38L	-
Lenovo ThinkSystem Storage 2U12 Chassis (with 2x PSUs)	7Y63CTO1WW*	BEY6	B38M	-
Lenovo ThinkSystem Storage 4U60 Chassis (with 2x PSUs)	7Y69CTO2WW	-	-	BQ9W

### Configuration notes:

For CTO models, two I/O expansion modules (\*feature code B4BS) are selected by default in the configurator, and the selection cannot be changed.

The models of the ThinkSystem DE240S, DE120S, and DE600S ship with the following items:

- One chassis with the following components:
  - Two I/O modules
  - Two power supplies
  - Two cooling modules (4U60 LFF only)
- Four 1 m MiniSAS HD 8644/MiniSAS HD 8644 cables (Models listed in Table 7)
- Rack Mount Kit
- *Quick Installation Guide*
- *Electronic Publications Flyer*
- CTO models: Customer-configured power cables

High level connectivity topology for the DE4800H 4U60 is shown in the following figure.




Figure 10. DE4800H 4U60 connectivity topology

High level connectivity topology for the DE4800H 2U24 is shown in the following figure.




Figure 11. DE4800H 2U24 connectivity topology

The following table lists ordering information for the supported expansion enclosure connectivity options.

Table 6. Expansion unit connectivity options

Part number	Feature code	Description	Maximum quantity per expansion
SAS connectivity cables			
00YL847	C3HZ	External MiniSAS HD 8644/MiniSAS HD 8644 0.5M Cable	4
00YL848	C3HY	External MiniSAS HD 8644/MiniSAS HD 8644 1M Cable	4
00YL849	AU18	External MiniSAS HD 8644/MiniSAS HD 8644 2M Cable	4
00YL850	AU19	External MiniSAS HD 8644/MiniSAS HD 8644 3M Cable	4

**Configuration notes:**

- Four SAS cables are needed per each expansion enclosure (two SAS cables per I/O Module) for connections to the controller enclosure and for daisy chaining of the expansion enclosures.
- The length of the SAS cables that connect a 2U24 or 2U12 enclosure to an adjacent 4U60 enclosure should be at least 1 meter.

## Drives

All drives are dual-port and hot-swappable. Drives of the same form factor can be intermixed within the appropriate enclosure, which provides the flexibility to address performance and capacity needs within a single enclosure.

More drives and expansion enclosures are designed to be dynamically added with virtually no downtime, which helps to quickly and seamlessly respond to ever-growing capacity demands.

The following table lists the specifications for drives in the DE4800H and DE4800F storage systems

Table 7. Drives specifications

Product Name	DE4800H LFF (7DCB)	DE4800H SFF (7DCR)	DE4800H LFF (7DCS)	DE4800F SFF (7DCC)
HDD Bay Type	3.5"	2.5"	3.5"	2.5"
HDD Type	SAS, SSD*	SAS, SSD*	SAS, SSD*	SSD
HDD Bay Quantity	12	24	60	24
Hot-Swap HDD Bays (Y/N)	Y	Y	Y	Y
Solid State Disk (SSD) Support	Y	Y	Y	Y
HDD Intermix (within enclosure)	Y	Y	Y	N
Maximum HDDs per System (System = Controller plus expansion enclosures)	300**	300**	300**	120

\*10K support, max 192 drives

\*\* Up to 120 SSD only

The following tables list the drive options for internal storage for each base enclosure and expansions.

The Lenovo ThinkSystem DE4800H Hybrid enclosures:

- [DE4800H Hybrid SAS 2U12](#)
- [DE4800H Hybrid SAS 2U24](#)
- [DE4800H Hybrid SAS 4U60](#)

The Lenovo ThinkSystem DE4800F All Flash enclosures::

- [DE4800F All Flash SAS 2U24](#)

ThinkSystem Expansion enclosures:

- [ThinkSystem DE120S 2U12 Exp](#)
- [ThinkSystem DE240S 2U24 Exp](#)
- [Thinksystem DE600S 4U60 Exp v2](#)

Table 8. 7DCBCTO1WW - DE4800H Hybrid SAS 2U12

Part number	Feature code	Description	Max Qty
<b>LFF drive options</b>			
4XB7A74947	BKUP	Lenovo ThinkSystem DE Series 1.92TB 1DWD 2.5" SSD 2U12 (2.5" drive in a 3.5" tray)	12
4XB7A74954	BKUJ	Lenovo ThinkSystem DE Series 3.84TB 1DWD 2.5" SSD 2U12 (2.5" drive in a 3.5" tray)	12
4XB7A88501	BWCI	Lenovo ThinkSystem DE Series 3.84TB 1DWD 2.5" SSD FIPS 2U12 (2.5" drive in a 3.5" tray)	12
4XB7A14099	B4C3	Lenovo ThinkSystem DE Series 4TB 7.2K 3.5" HDD 2U12	12
4XB7A14102	B4C6	Lenovo ThinkSystem DE Series 10TB 7.2K 3.5" HDD 2U12	12
4XB7A14103	B4C7	Lenovo ThinkSystem DE Series 10TB 7.2K 3.5" HDD SED FIPS 2U12	12
4XB7A88027	BW1W	Lenovo ThinkSystem DE Series 22TB 7.2K 3.5" HDD 2U12	12
4XB7B03838	C7XS	Lenovo ThinkSystem DE Series 24TB 7.2K 3.5" HDD 2U12	12

Table 9. 7DCRCTO1WW - DE4800H Hybrid SAS 2U24

Part number	Feature code	Description	Max Qty
<b>SFF drive options</b>			
4XB7A74951	BKUT	Lenovo ThinkSystem DE Series 1.92TB 1DWD 2.5" SSD 2U24	24
4XB7A88046	BW12	Lenovo ThinkSystem DE Series 2.4TB 10K 2.5" HDD 2U24	24
4XB7A88048	BW13	Lenovo ThinkSystem DE Series 2.4TB 10K 2.5" HDD FIPS 2U24	24
4XB7A74955	BKUK	Lenovo ThinkSystem DE Series 3.84TB 1DWD 2.5" SSD 2U24	24
4XB7A88469	BWCJ	Lenovo ThinkSystem DE Series 3.84TB 1DWD 2.5" SSD FIPS 2U24	24
4XB7A14176	B4RY	Lenovo DE Series 7.68TB 1DWD 2.5" SSD 2U24	24
4XB7A88466	BW2B	Lenovo ThinkSystem DE Series 15.36TB 1DWD 2.5" SSD SED 2U24	24

Table 10. 7DCSCTO1WW - DE4800H Hybrid SAS 4U60

Part number	Feature code	Description	Max Qty
<b>LFF drive options</b>			
4XB7A86719	BUC8	Lenovo ThinkSystem DE Series 1.92TB 1DWD SAS SSD 4U60 (2.5" drive in a 3.5" tray)	60
4XB7A88506	BWCM	Lenovo ThinkSystem DE Series 3.84TB 1DWD 2.5" SSD FIPS 4U60 (2.5" drive in a 3.5" tray)	60
4XB7A14124	B4GG	Lenovo ThinkSystem DE Series 4TB 7.2K 3.5" HDD 4U60	60
4XB7A14126	B4GJ	Lenovo ThinkSystem DE Series 10TB 7.2K 3.5" HDD 4U60	60
4XB7A14127	B4GK	Lenovo ThinkSystem DE Series 10TB 7.2K 3.5" HDD SED FIPS 4U60	60
4XB7A88038	BW1Y	Lenovo ThinkSystem DE Series 22TB 7.2K 3.5" HDD 4U60	60
4XB7B03894	C7XT	Lenovo ThinkSystem DE Series 24TB 7.2K 3.5" HDD 4U60	60
<b>Drive pack options</b>			
4XB7A86720	BUC9	Lenovo ThinkSystem DE Series 38.4TB Pack (20x 1.92TB SAS SSDs) (2.5" drive in a 3.5" tray)	3
4XB7A88507	BWCN	Lenovo ThinkSystem DE Series 76.8TB FIPS Pack (20x 3.84TB FIPS SSDs) (2.5" drive in a 3.5" tray)	3
4XB7A14163	B4GN	Lenovo ThinkSystem DE Series 80TB HDD Pack (20x 4TB HDD)	3
4XB7A14167	B4GQ	Lenovo ThinkSystem DE Series 200TB HDD Pack (20x 10TB HDD)	3
4XB7A14169	B4GR	Lenovo ThinkSystem DE Series 200TB HDD SED FIPS Pack (20x 10TB HDD)	3
4XB7A88042	BW1K	Lenovo ThinkSystem DE Series 440TB HDD Pack (20x 22TB)	3
4XB7B03895	C7XU	Lenovo ThinkSystem DE Series 480TB HDD Pack (20x 24TB HDDs)	3

Table 11. 7DCCCTO1WW - DE4800F All Flash SAS 2U24

Part number	Feature code	Description	Max Qty
<b>SFF drive options</b>			
4XB7A74951	BKUT	Lenovo ThinkSystem DE Series 1.92TB 1DWD 2.5" SSD 2U24	24
4XB7A74955	BKUK	Lenovo ThinkSystem DE Series 3.84TB 1DWD 2.5" SSD 2U24	24
4XB7A88469	BWCJ	Lenovo ThinkSystem DE Series 3.84TB 1DWD 2.5" SSD FIPS 2U24	24
4XB7A14176	B4RY	Lenovo DE Series 7.68TB 1DWD 2.5" SSD 2U24	24
4XB7A88466	BW2B	Lenovo ThinkSystem DE Series 15.36TB 1DWD 2.5" SSD SED 2U24	24
<b>Drive pack options</b>			
4XB7A74952	BKUU	Lenovo ThinkSystem DE Series 23.04TB Pack (12x 1.92TB SSD)	2
4XB7A74956	BKUL	Lenovo ThinkSystem DE Series 46.08TB Pack (12x 3.84TB SSD)	2
4XB7A88470	BWCK	Lenovo ThinkSystem DE Series 46TB FIPS Pack (12x 3.84TB FIPS SSDs)	2
4XB7A14238	B4RW	Lenovo ThinkSystem DE Series 92TB SSD Pack (12x 7.68TB SSD)	2
4XB7A88467	BW2C	Lenovo ThinkSystem DE Series 184.3TB Pack (12x 15.36TB SED SSD)	2

Table 12. 7Y63CTO1WW - ThinkSystem DE120S 2U12 Expansion

Part number	Feature code	Description	Max Qty
<b>LFF drive options</b>			
4XB7A74946	BKUN	Lenovo ThinkSystem DE Series 960GB 1DWD 2.5" SSD 2U12 (2.5" drive in a 3.5" tray)	12
4XB7A74947	BKUP	Lenovo ThinkSystem DE Series 1.92TB 1DWD 2.5" SSD 2U12 (2.5" drive in a 3.5" tray)	12
4XB7A74954	BKUJ	Lenovo ThinkSystem DE Series 3.84TB 1DWD 2.5" SSD 2U12 (2.5" drive in a 3.5" tray)	12
4XB7A88501	BWCI	Lenovo ThinkSystem DE Series 3.84TB 1DWD 2.5" SSD FIPS 2U12 (2.5" drive in a 3.5" tray)	12
4XB7A14099	B4C3	Lenovo ThinkSystem DE Series 4TB 7.2K 3.5" HDD 2U12	12
4XB7A14101	B4C5	Lenovo ThinkSystem DE Series 8TB 7.2K 3.5" HDD 2U12	12
4XB7A14102	B4C6	Lenovo ThinkSystem DE Series 10TB 7.2K 3.5" HDD 2U12	12
4XB7A14103	B4C7	Lenovo ThinkSystem DE Series 10TB 7.2K 3.5" HDD SED FIPS 2U12	12
4XB7A14104	B4C8	Lenovo ThinkSystem DE Series 12TB 7.2K 3.5" HDD 2U12	12
4XB7A74942	BHDP	Lenovo ThinkSystem DE Series 18TB 7.2K 3.5" HDD 2U12	12
4XB7A88027	BW1W	Lenovo ThinkSystem DE Series 22TB 7.2K 3.5" HDD 2U12	12
4XB7B03838	C7XS	Lenovo ThinkSystem DE Series 24TB 7.2K 3.5" HDD 2U12	12

Table 13. 7Y68CTO1WW - ThinkSystem DE240S 2U24 Expansion

Part number	Feature code	Description	Max Qty
<b>SFF drive options</b>			
4XB7A74948	BKUQ	Lenovo ThinkSystem DE Series 960GB 1DWD 2.5" SSD 2U24	24
4XB7A14112	B4BY	Lenovo ThinkSystem DE Series 1.2TB 10K 2.5" HDD 2U24	24
4XB7A14113	B4BZ	Lenovo ThinkSystem DE Series 1.8TB 10K 2.5" HDD 2U24	24
4XB7A14114	B4C0	Lenovo ThinkSystem DE Series 1.8TB 10K 2.5" HDD SED FIPS 2U24	24
4XB7A88046	BW12	Lenovo ThinkSystem DE Series 2.4TB 10K 2.5" HDD 2U24	24
4XB7A88048	BW13	Lenovo ThinkSystem DE Series 2.4TB 10K 2.5" HDD FIPS 2U24	24
4XB7A74955	BKUK	Lenovo ThinkSystem DE Series 3.84TB 1DWD 2.5" SSD 2U24	24
4XB7A14176	B4RY	Lenovo DE Series 7.68TB 1DWD 2.5" SSD 2U24	24
4XB7A14110	B4CD	Lenovo ThinkSystem DE Series 15.36TB 1DWD 2.5" SSD 2U24	24
4XB7A88466	BW2B	Lenovo ThinkSystem DE Series 15.36TB 1DWD 2.5" SSD SED 2U24	24
<b>Drive pack options</b>			
4XB7A74949	BKUR	Lenovo ThinkSystem DE Series 11.52TB Pack (12x 960GB SSD)	2
4XB7A74952	BKUU	Lenovo ThinkSystem DE Series 23.04TB Pack (12x 1.92TB SSD)	2
4XB7A74956	BKUL	Lenovo ThinkSystem DE Series 46.08TB Pack (12x 3.84TB SSD)	2
4XB7A88470	BWCK	Lenovo ThinkSystem DE Series 46TB FIPS Pack (12x 3.84TB FIPS SSDs)	2



Table 14. 7Y69CTO2WW - Thinksystem DE600S 4U60 Expansion v2

Part number	Feature code	Description	Max Qty
<b>LFF drive options</b>			
4XB7A86719	BUC8	Lenovo ThinkSystem DE Series 1.92TB 1DWD SAS SSD 4U60 (2.5" drive in a 3.5" tray)	60
4XB7A88506	BWCM	Lenovo ThinkSystem DE Series 3.84TB 1DWD 2.5" SSD FIPS 4U60 (2.5" drive in a 3.5" tray)	60
4XB7A14124	B4GG	Lenovo ThinkSystem DE Series 4TB 7.2K 3.5" HDD 4U60	60
4XB7A14126	B4GJ	Lenovo ThinkSystem DE Series 10TB 7.2K 3.5" HDD 4U60	60
4XB7A14127	B4GK	Lenovo ThinkSystem DE Series 10TB 7.2K 3.5" HDD SED FIPS 4U60	60
4XB7A14125	B4GH	Lenovo ThinkSystem DE Series 8TB 7.2K 3.5" HDD 4U60	60
4XB7A14128	B4GL	Lenovo ThinkSystem DE Series 12TB 7.2K 3.5" HDD 4U60	60
4XB7A74943	BHDQ	Lenovo ThinkSystem DE Series 18TB 7.2K 3.5" HDD 4U60	60
4XB7A88038	BW1Y	Lenovo ThinkSystem DE Series 22TB 7.2K 3.5" HDD 4U60	60
4XB7B03894	C7XT	Lenovo ThinkSystem DE Series 24TB 7.2K 3.5" HDD 4U60	60
<b>Drive pack options</b>			
4XB7A86720	BUC9	Lenovo ThinkSystem DE Series 38.4TB Pack (20x 1.92TB SAS SSDs) (2.5" drive in a 3.5" tray)	3
4XB7A88507	BWCN	Lenovo ThinkSystem DE Series 76.8TB FIPS Pack (20x 3.84TB FIPS SSDs) (2.5" drive in a 3.5" tray)	3
4XB7A14163	B4GN	Lenovo ThinkSystem DE Series 80TB HDD Pack (20x 4TB HDD)	3
4XB7A14165	B4GP	Lenovo ThinkSystem DE Series 160TB HDD Pack (20x 8TB HDD)	3
4XB7A14167	B4GQ	Lenovo ThinkSystem DE Series 200TB HDD Pack (20x 10TB HDD)	3
4XB7A14169	B4GR	Lenovo ThinkSystem DE Series 200TB HDD SED FIPS Pack (20x 10TB HDD)	3
4XB7A14171	B4GS	Lenovo ThinkSystem DE Series 240TB HDD Pack (20x 12TB HDD)	3
4XB7A74944	BHDR	Lenovo ThinkSystem DE Series 360TB HDD Pack (20x 18TB HDDs)	3
4XB7A88042	BW1K	Lenovo ThinkSystem DE Series 440TB HDD Pack (20x 22TB)	3
4XB7B03895	C7XU	Lenovo ThinkSystem DE Series 480TB HDD Pack (20x 24TB HDDs)	3

**Shipping requirement:** 2U12 and 2U24 enclosures can be shipped with all drive bays populated, however the 4U60 enclosures must be shipped with drives removed.

**Configuration notes:**

- For hybrid (HDDs and SSDs) and all flash (SSDs only) storage configurations, a single ThinkSystem DE4800H storage system can support a maximum of 120 SSDs.
- A minimum of 20 drives is required for each 4U60 LFF enclosure (the front row of each drawer must be populated with four drives).
- Intermix of FIPS drives and non-FIPS drives is supported within the system.
- FIPS drives are not available in the following countries:
  - Belarus
  - Kazakhstan
  - People's Republic of China
  - Russia

**Software**

The following functions are included with every Lenovo ThinkSystem DE4800H and DE4800F:

- **RAID levels 0, 1, 3, 5, 6, and 10** : Provide the flexibility to choose the level of performance and data protection required.
- **Dynamic Disk Pools (DDP) technology**: Helps improve performance and availability with significantly faster rebuild time and reduced exposure to multiple drive failures by allowing data and built-in spare capacity to be distributed across all physical drives in the storage pool.
- **All Flash Array (AFA) capability** : Meets the demand for higher speed storage and provide higher IOPS and bandwidth with lower power usage and total cost of ownership than hybrid or HDD-based solutions.
- **SSD Read Cache** : Helps accelerate performance of read-centric workloads.
- **Thin provisioning**: Optimizes efficiency of Dynamic Disk Pools by allocating storage space based on the minimum space required by each application at any given time, so that applications consume only the space they are actually using, not the total space that has been allocated to them, which allows customers to purchase storage they need today and add more as application requirements grow.
- **Snapshots**: Enables creation of copies of data for backup, parallel processing, testing, and development, and have the copies available almost immediately (up to 512 snapshot targets per system).
- **Encryption**: Provides encryption for data at rest for enhanced data security with the optional FIPS 140-2 Level 2 drives and embedded key management (AES-256) or an external key management server.
- **Automatic load balancing**: Provides automated I/O workload balancing of I/O traffic from the hosts across both controllers.
- **Data assurance**: Ensures industry-standard T10-PI end-to-end data integrity in the storage system (from the host ports to the drives).
- **Dynamic volume and capacity expansion**: Allows the capacity of a volume to be expanded by adding new physical drives or making use of unused space on existing drives.

The Lenovo ThinkSystem DE4800H and DE4800F capabilities can be expanded with optional licensed functions. Optional licensed functions include:

- **Snapshots upgrade**: Increase the supported number of snapshots up to 512.
- **Scalability to 300 drives (future planned: 480 drives)**: Increases the number of supported 4U60 LFF expansion enclosures to 4 for up to 300 LFF drives per system (future planned 7x 4U60 expansions, up to 480 LFF drives per system).
- **Synchronous mirroring**: Provides storage system-based online, real-time data replication between the storage systems containing primary (local) and secondary (remote) volumes by using synchronous data transfers over Fibre Channel communication links (both storage systems must have licenses for synchronous mirroring).
- **Asynchronous mirroring**: Provides storage system-based data replication between the storage systems containing primary (local) and secondary (remote) volumes by using asynchronous data transfers over Fibre Channel communication links at set intervals (both storage systems must have licenses for asynchronous mirroring).

**Note:** The synchronous and asynchronous mirroring features of the ThinkSystem DE4800H and DE4800F interoperate with other ThinkSystem DE Series storage arrays.

The following table lists the Feature on Demand (FoD) upgrades for the ThinkSystem DE4800H and DE4800F to enable optional software features. Each optional DE4800H and DE4800F function is licensed on a per-system basis and covers both controller enclosure and all attached expansion enclosures.

Table 15. DE4800H optional software features

Description	Part number	Feature code
Lenovo ThinkSystem DE4800H Base Bundle	CTO only	C663
Lenovo Thinksystem DE4800H Asynchronous Mirroring	4L47A95690	C3HP
Lenovo Thinksystem DE4800H Snapshot Upgrade 512	4L47A95689	C3HN
Lenovo Thinksystem DE4800 Synchronous Mirroring	4L47A95691	C3J7

Table 16. DE4800F optional software features

Description	Part number	Feature code
Lenovo ThinkSystem DE4800F Premium Bundle	CTO only	C664
Lenovo Thinksystem DE4800 Synchronous Mirroring	4L47A95691	C3J7

Software maintenance is included in the ThinkSystem DE4800H and DE4800F base warranty and optional warranty extensions, which provides 3-year software support with the option to extend it up to 5 years in 1-year or 2-year increments (see [Warranty and support](#) for details).

## Management

The DE4800H and DE4800F supports the following management interfaces:

- ThinkSystem System Manager, a web-based interface via HTTPS for single-system management, that runs on the storage system itself and requires only a supported browser, so there is no need for a separate console or plug-in. For more information, see the [System Manager Online Help](#).
- ThinkSystem SAN Manager, a host-installed GUI-based application, for centralized management of multiple storage systems. For more information, see the [SAN Manager Online Help](#).
- ThinkSystem DE Series Storage Plugin for vCenter. For more information, see the [DE Series vCenter Plugin Online Help](#).
- Command line interface (CLI) via SSH or through serial console. For more information, see the [CLI Online Help](#).
- Syslog, SNMP, and e-mail notifications.
- Optional Lenovo XClarity Administrator support for discovery, inventory, and monitoring.

## Power supplies and cables

The ThinkSystem DE Series 2U24 SFF and 2U12 LFF enclosures ship with two redundant hot-swap 913W (100-240V) Platinum AC power supplies, each with an IEC 320-C14 connector.

The ThinkSystem DE Series 4U60 LFF enclosures ship with two redundant hot-swap 2325 W (200 - 240 V) Platinum AC power supplies, each with an IEC 320-C20 connector.

The CTO models require the selection of two power cables.

The following table lists the rack power cable and line cord options that can be ordered for the DE Series 2U24 SFF enclosures (two power cords per enclosure).

Table 17. Power cables for DE Series 2U24 SFF and 2U12 LFF enclosures

Part number	Feature code	Description
<b>Rack power cables</b>		
00Y3043	A4VP	1.0m, 10A/100-250V, C13 to C14 Jumper Cord
4L67A08367	B0N5	1.0m, 13A/100-250V, C13 to C14 Jumper Cord
39Y7937	6201	1.5m, 10A/100-250V, C13 to C14 Jumper Cord
4L67A08368	B0N6	1.5m, 13A/100-250V, C13 to C14 Jumper Cord
4L67A08365	B0N4	2.0m, 10A/100-250V, C13 to C14 Jumper Cord
4L67A08369	6570	2.0m, 13A/100-250V, C13 to C14 Jumper Cord
4L67A08366	6311	2.8m, 10A/100-250V, C13 to C14 Jumper Cord
4L67A08370	6400	2.8m, 13A/100-250V, C13 to C14 Jumper Cord
39Y7938	6204	2.8m, 10A/100-250V, C13 to IEC 320-C20 Rack Power Cable
39Y7932	6263	4.3m, 10A/100-250V, C13 to C14 Jumper Cord
4L67A08371	6583	4.3m, 13A/100-250V, C13 to C14 Rack Power Cable
<b>Line cords</b>		
39Y7930	6222	2.8m, 10A/250V, C13 to IRAM 2073 (Argentina) Line Cord
81Y2384	6492	4.3m 10A/220V, C13 to IRAM 2073 (Argentina) Line Cord
39Y7924	6211	2.8m, 10A/250V, C13 to AS/NZ 3112 (Australia/NZ) Line Cord
81Y2383	6574	4.3m, 10A/230V, C13 to AS/NZS 3112 (Aus/NZ) Line Cord
69Y1988	6532	2.8m, 10A/250V, C13 to NBR 14136 (Brazil) Line Cord
81Y2387	6404	4.3m, 10A/250V, C13 - 2P+Gnd (Brazil) Line Cord
39Y7928	6210	2.8m, 10A/220V, C13 to GB 2099.1 (China) Line Cord
81Y2378	6580	4.3m, 10A/220V, C13 to GB 2099.1 (China) Line Cord
39Y7918	6213	2.8m, 10A/250V, C13 to DK2-5a (Denmark) Line Cord
81Y2382	6575	4.3m, 10A/230V, C13 to DK2-5a (Denmark) Line Cord
39Y7917	6212	2.8m, 10A/230V, C13 to CEE7-VII (Europe) Line Cord
81Y2376	6572	4.3m, 10A/230V, C13 to CEE7-VII (Europe) Line Cord
39Y7927	6269	2.8m, 10A/250V, C13(2P+Gnd) (India) Line Cord
81Y2386	6567	4.3m, 10A/240V, C13 to IS 6538 (India) Line Cord
39Y7920	6218	2.8m, 10A/250V, C13 to SI 32 (Israel) Line Cord
81Y2381	6579	4.3m, 10A/230V, C13 to SI 32 (Israel) Line Cord
39Y7921	6217	2.8m, 220-240V, C13 to CEI 23-16 (Italy/Chile) Line Cord
81Y2380	6493	4.3m, 10A/230V, C13 to CEI 23-16 (Italy/Chile) Line Cord
46M2593	A1RE	2.8m, 12A/125V, C13 to JIS C-8303 (Japan) Line Cord

Part number	Feature code	Description
39Y7926	6335	4.3m, 12A/100V, C13 to JIS C-8303 (Japan) Line Cord
4L67A08362	6495	4.3m, 12A/200V, C13 to JIS C-8303 (Japan) Line Cord
39Y7925	6219	2.8m, 220-240V, C13 to KETI (S Korea) Line Cord
81Y2385	6494	4.3m, 12A/220V, C13 to KSC 8305 (S. Korea) Line Cord
39Y7922	6214	2.8m, 10A/250V, C13 to SABS 164 (S Africa) Line Cord
81Y2379	6576	4.3m, 10A/230V, C13 to SABS 164 (South Africa) Line Cord
39Y7919	6216	2.8m, 10A/250V, C13 to SEV 1011-S24507 (Swiss) Line Cord
81Y2390	6578	4.3m, 10A/230V, C13 to SEV 1011-S24507 (Sws) Line Cord
23R7158	6386	2.8m, 10A/125V, C13 to CNS 10917-3 (Taiwan) Line Cord
81Y2375	6317	2.8m, 10A/240V, C13 to CNS 10917-3 (Taiwan) Line Cord
81Y2374	6402	2.8m, 13A/125V, C13 to CNS 60799 (Taiwan) Line Cord
4L67A08363	AX8B	4.3m, 10A 125V, C13 to CNS 10917 (Taiwan) Line Cord
81Y2389	6531	4.3m, 10A/250V, C13 to 76 CNS 10917-3 (Taiwan) Line Cord
81Y2388	6530	4.3m, 13A/125V, C13 to CNS 10917 (Taiwan) Line Cord
39Y7923	6215	2.8m, 10A/250V, C13 to BS 1363/A (UK) Line Cord
81Y2377	6577	4.3m, 10A/230V, C13 to BS 1363/A (UK) Line Cord
90Y3016	6313	2.8m, 10A/120V, C13 to NEMA 5-15P (US) Line Cord
46M2592	A1RF	2.8m, 10A/250V, C13 to NEMA 6-15P Line Cord
00WH545	6401	2.8m, 13A/120V, C13 to NEMA 5-15P (US) Line Cord
4L67A08359	6370	4.3m, 10A/125V, C13 to NEMA 5-15P (US) Line Cord
4L67A08361	6373	4.3m, 10A/250V, C13 to NEMA 6-15P (US) Line Cord
4L67A08360	AX8A	4.3m, 13A/120V, C13 to NEMA 5-15P (US) Line Cord

The following table lists the rack power cable and line cord options that can be ordered for the DE Series 4U60 LFF enclosures (two power cords per enclosure).

Table 18. Power cables for DE Series 4U60 enclosures

Part number	Feature code	Description
<b>Rack power cables</b>		
4L67A86680	B4L2	2.0m, 16A/100-250V, C19 to C20 Jumper Cord
39Y7916	6252	2.5m, 16A/100-240V, C19 to IEC 320-C20 Rack Power Cable
<b>Line cords</b>		
40K9777	6276	C19 4.3 meter Line Cord - Argentina
40K9773	6284	C19 4.3 meter Line Cord - Australia/NZ
40K9775	6277	C19 4.3 meter Line Cord - Brazil
40K9774	6288	C19 4.3 meter Line Cord - China
40K9769	6283	C19 4.3 meter Line Cord - Dmk/Swiss
40K9766	6279	C19 4.3 meter Line Cord - Europe
40K9776	6285	C19 4.3 meter Line Cord - India
40K9771	6282	C19 4.3 meter Line Cord - Israel
40K9768	6281	C19 4.3 meter Line Cord - Italy
41Y9233	6291	Japan 15A/200V C19/JIS C-8303 4.3m line cord
41Y9231	6289	4.3m, 15A/250V, C19 to KSC 8305 (S. Korea) Line Cord
40K9770	6280	C19 4.3 meter Line Cord - S Africa
40K9767	6278	C19 4.3 meter Line Cord - UK
00D7197	A1NV	4.3m, 15A/250V, C19 to NEMA 6-15P (US) Line Cord
40K9772	6275	C19 4.3m cord - NEMA L6-20P

## Rack installation

The individually shipped ThinkSystem DE Series 2U12 enclosures come with the ThinkSystem Storage Rack Mount Kit 2U12, and the individually shipped ThinkSystem DE Series 2U24 and 4U60 enclosures come with the ThinkSystem Storage Rack Mount Kit 2U24/4U60. These rack mount kits are listed in the following table.

Table 19. 4-post rack mount kits

Description	Feature code	Quantity
Lenovo ThinkSystem Storage Rack Mount Kit 2U12	B38X	1
Lenovo ThinkSystem Storage Rack Mount Kit 2U24/4U60	B38Y	1

When the ThinkSystem DE Series enclosures are factory-integrated and shipped installed in a rack cabinet, the rack mount kits that support Ship-in-Rack (SIR) capabilities are derived by the configurator. The SIR-capable rack mount kits are listed in the following table.

Table 20. 4-post SIR rack mount kits

Description	Feature code	Quantity
Lenovo ThinkSystem Storage Rack Mount Kit 2U12	B38X	1
Lenovo ThinkSystem Storage SIR Rack Mount Kit (for 2U24 enclosures)	B6TH	1
DM/DE 4U Adjustable Rail Kit (SIR)	B742	1

The following table summarizes the rack mount kit features and specifications.

Table 21. Rack mount kit features and specifications summary

Attribute	Screw-in fixed rail with adjustable depth			
	2U12	2U24/4U60	2U24 SIR	4U SIR
Feature code	B38X	B38Y	B6TH	B742
Enclosure support	DE120S	DE4800H 2U DE4800H 4U† DE240S DE600S‡	DE4800H 2U DE240S	DE4800H 4U‡ DE600S‡
Rail type	Fixed (static) with adjustable depth	Fixed (static) with adjustable depth	Fixed (static) with adjustable depth	Fixed (static) with adjustable depth
Tool-less installation	No	No	No	No
In-rack maintenance	Yes*	Yes*	Yes*	Yes*
Ship-in-rack (SIR) support	Yes	No	Yes	Yes
1U PDU support	Yes	Yes	Yes	Yes
0U PDU support	Limited**	Limited**	Limited**	Limited**
Rack type	IBM or Lenovo 4-post, IEC standard-compliant	IBM or Lenovo 4-post, IEC standard-compliant	IBM or Lenovo 4-post, IEC standard-compliant	IBM or Lenovo 4-post, IEC standard-compliant
Mounting holes	Square or round	Square or round	Square or round	Square or round
Mounting flange thickness	2 mm (0.08 in.) – 3.3 mm (0.13 in.)	2 mm (0.08 in.) – 3.3 mm (0.13 in.)	2 mm (0.08 in.) – 3.3 mm (0.13 in.)	2 mm (0.08 in.) – 3.3 mm (0.13 in.)
Distance between front and rear mounting flanges <sup>^</sup>	605 mm (23.8 in.) – 812.8 mm (32 in.)	605 mm (23.8 in.) – 812.8 mm (32 in.)	605 mm (23.8 in.) – 812.8 mm (32 in.)	605 mm (23.8 in.) – 812.8 mm (32 in.)



‡ The rack cabinet must be at least 1100 mm (43.31 in.) deep for 4U60 enclosures.

\* The majority of the enclosure components can be serviced from the front or rear of the enclosure, which does not require the removal of the enclosure from the rack cabinet.

\*\* If a 0U PDU is used, the rack cabinet must be at least 1000 mm (39.37 in.) deep for 2U12 and 2U24 enclosures, or at least 1200 mm (47.24 in.) deep for 4U60 enclosures.

^ Measured when mounted on the rack, from the front surface of the front mounting flange to the rear most point of the rail.

## Physical specifications

The ThinkSystem DE Series 2U12 LFF (7DCB / 7Y63) enclosures have the following dimensions:

- Height: 87 mm (3.4 in.)
- Width: 447 mm (17.6 in.)
- Depth: 536 mm (21.1 in.)

The ThinkSystem DE Series 2U24 SFF (7DCR / 7DCC / 7Y68) enclosures have the following dimensions:

- Height: 85 mm (3.4 in.)
- Width: 447 mm (17.6 in.)
- Depth: 511 mm (20.1 in.)

The ThinkSystem DE Series 4U60 LFF (7DCS / 7Y69) enclosures have the following dimensions:

- Height: 174 mm (6.9 in.)
- Width: 449 mm (17.7 in.)
- Depth: 922 mm (36.3 in.)

Weights of enclosures (fully configured):

- DE4800H 2U12 LFF controller enclosure (7DCB): 25.07 kg (55.3 lb)
- DE4800H 2U24 SFF controller enclosure (7DCR): 25.07 kg (55.3 lb)
- DE4800H 4U60 LFF controller enclosure (7DCS): 108.49 kg (239.2 lb)
- DE4800F 2U24 SFF controller enclosure (7DCC): 25.07 kg (55.3 lb)
- DE120S 2U12 LFF expansion enclosure (7Y63): 27.12 kg (59.8 lb)
- DE240S 2U24 SFF expansion enclosure (7Y68): 27.44 kg (60.5 lb)
- DE600S 4U60 LFF expansion enclosure (7Y69): 112.2 kg (247.4 lb)

## Operating environment

The ThinkSystem DE Series 2U24 SFF and 4U60 LFF enclosures are supported in the following environment:

- Air temperature:
  - Operating:
    - DE4800H / DE4800F and DE240S 2U24 SFF: 5 °C - 45 °C (41 °F - 113 °F)
    - DE4800H and DE600S 4U60 LFF: 10 °C - 40 °C (50 °F - 104 °F)
    - DE120S 2U12 LFF: 10 °C - 40 °C (50 °F - 104 °F)
  - Non-operating: -10 °C - +50 °C (14 °F - 122 °F)
  - Maximum altitude: 3050 m (10,000 ft)
- Relative humidity:
  - Operating: 8% - 90% (non-condensing)
  - Non-operating: 10% - 90% (non-condensing)
- Electrical power:
  - 100 to 127 V AC (nominal); 50 Hz / 60 Hz (except 4U60 LFF enclosures)
  - 200 to 240 V AC (nominal); 50 Hz / 60 Hz
- Acoustical noise emission:
  - DE4800H/F 2U24 SFF, DE4800H 4U60 and DE600S 4U60 SFF: 7.2 bels
  - DE240S 2U24 SFF and DE120S 2U12 LFF: 6.6 bels

The following table lists the maximum enclosure power load, inlet current, and heat output based on the source voltage.

Table 22. Enclosure power load, inlet current, and heat output

Enclosure	Source voltage (nominal)	Maximum power load	Current per inlet	Heat output
DE4800H/F 2U24 SFF	100 - 127 V AC	409 W	5.35 A	1733 BTU/hour
	200 - 240 V AC	534 W	2.43 A	1821 BTU/hour
DE4800H 4U60 LFF	200 - 240 V AC	1541 W	16.22 A	5258 BTU/hour
DE240S 2U24 SFF	100 - 127 V AC	389 W	4.1 A	1328 BTU/hour
	200 - 240 V AC	382 W	2.02 A	1304 BTU/hour
DE120S 2U12 LFF	100 - 127 V AC	306 W	3.3 A	1045 BTU/hour
	200 - 240 V AC	300 W	1.58 A	1024 BTU/hour
DE600S 4U60 LFF	200 - 240 V AC	1446 W	7.62 A	4934 BTU/hour

## Warranty and support

The ThinkSystem DE Series enclosures have a three-year customer-replaceable unit (CRU) and onsite limited (for field-replaceable units [FRUs] only) warranty with standard call center support during normal business hours and 9x5 Next Business Day Parts Delivered.

Lenovo's additional support services provide a sophisticated, unified support structure for a customer's data center, with an experience consistently ranked number one in customer satisfaction worldwide.

The following Lenovo support services are available:

- **Premier Support** provides a Lenovo-owned customer experience and delivers direct access to technicians skilled in hardware, software, and advanced troubleshooting, in addition to the following capabilities:
  - Direct technician-to-technician access through a dedicated phone line.
  - 24x7x365 remote support.
  - Single point of contact service.
  - End to end case management.
  - 3rd Party collaborative software support.
  - Online case tools and live chat support.
  - On-demand remote system analysis.
- **Warranty Upgrades (Preconfigured Support)** are available to meet the on-site response time targets that match the criticality of customer's systems:
  - 3, 4, or 5 years of service coverage.
  - 1-year or 2-year post-warranty extensions.
  - **Foundation Service:** 9x5 service coverage with next business day onsite response, with optional YourDrive YourData.
  - **Essential Service:** 24x7 service coverage with 4-hour onsite response or 24-hour committed repair (available only in select regions), with optional YourDrive YourData.
  - **Advanced Service:** 24x7 service coverage with 2-hour onsite response or 6-hour committed repair (available only in select regions), with optional YourDrive YourData.
- **Managed Services**

Lenovo Managed Services provide continuous 24x7 remote monitoring (plus 24x7 call center availability) and proactive management of a customer's data center using state of the art tools, systems, and practices by a team of highly skilled and experienced Lenovo services professionals.

Quarterly reviews check error logs, verify firmware and operating system device driver levels, and software as needed. Lenovo will also maintain records of latest patches, critical updates, and firmware levels, to ensure customer's systems are providing business value through optimized performance.
- **Technical Account Management (TAM)**

A Lenovo Technical Account Manager helps customers optimize operations of their data centers based on a deep understanding of customer's business. Customers gain direct access to a Lenovo TAM, who serves as their single point of contact to expedite service requests, provide status updates, and furnish reports to track incidents over time. Also, a TAM helps proactively make service recommendations and manage service relationship with Lenovo to make certain that customer's needs are met.
- **YourDrive YourData**

Lenovo's YourDrive YourData service is a multi-drive retention offering that ensures that customer's data is always under their control, regardless of the number of drives that are installed in their Lenovo system. In the unlikely event of a drive failure, customers retain possession of their drive while Lenovo replaces the failed drive part. Customer's data stays safely on customer premises, in their hands. The YourDrive YourData service can be purchased in convenient bundles with Foundation, Essential, or Advanced Service upgrades and extensions.

- **Health Check**

Having a trusted partner who can perform regular and detailed health checks is central to maintaining efficiency and ensuring that customer systems and business are always running at their best. Health Check supports Lenovo-branded server, storage, and networking devices, as well as select Lenovo-supported products from other vendors that are sold by Lenovo or a Lenovo-Authorized Reseller.

Some regions might have different warranty terms and conditions than the standard warranty. This is due to local business practices or laws in the specific region. Local service teams can assist in explaining region-specific terms when needed. Examples of region-specific warranty terms are second or longer business day parts delivery or parts-only base warranty.

If warranty terms and conditions include onsite labor for repair or replacement of parts, Lenovo will dispatch a service technician to the customer site to perform the replacement. Onsite labor under base warranty is limited to labor for replacement of parts that have been determined to be field-replaceable units (FRUs). Parts that are determined to be customer-replaceable units (CRUs) do not include onsite labor under base warranty.

If warranty terms include parts-only base warranty, Lenovo is responsible for delivering only replacement parts that are under base warranty (including FRUs) that will be sent to a requested location for self-service. Parts-only service does not include a service technician being dispatched onsite. Parts must be changed at customer's own cost and labor and defective parts must be returned following the instructions supplied with the spare parts.

Lenovo support services are region-specific. Not all support services are available in every region. For information about Lenovo support services that are available in a specific region, refer to the following resources:

- Service part numbers in Data Center Solution Configurator (DCSC):  
<http://dcsc.lenovo.com/#!/services>
- Lenovo Services Availability Locator  
<https://lenovolocator.com/>

For service definitions, region-specific details, and service limitations, refer to the following documents:

- Lenovo Statement of Limited Warranty for Infrastructure Solutions Group (ISG) Servers and System Storage  
<http://pcsupport.lenovo.com/us/en/solutions/ht503310>
- Lenovo Data Center Services Agreement  
<http://support.lenovo.com/us/en/solutions/ht116628>

## Services

Lenovo Data Center Services empower you at every stage of your IT lifecycle. From expert advisory and strategic planning to seamless deployment and ongoing support, we ensure your infrastructure is built for success. Our comprehensive services accelerate time to value, minimize downtime, and free your IT staff to focus on driving innovation and business growth.

**Note:** Some service options may not be available in all markets or regions. For more information, go to <https://lenovolocator.com/>. For information about Lenovo service upgrade offerings that are available in your region, contact your local Lenovo sales representative or business partner.

In this section:

- [Lenovo Advisory Services](#)
- [Lenovo Plan & Design Services](#)
- [Lenovo Deployment, Migration, and Configuration Services](#)
- [Lenovo Support Services](#)
- [Lenovo Managed Services](#)
- [Lenovo Sustainability Services](#)

## Lenovo Advisory Services

Lenovo Advisory Services simplify the planning process, enabling customers to build future-proofed strategies in as little as six weeks. Consultants provide guidance on projects including VM migration, storage, backup and recovery, and cost management to accelerate time to value, improve cost efficiency, and build a flexibly scalable foundation.

- **Assessment Services**

An Assessment helps solve your IT challenges through an onsite, multi-day session with a Lenovo technology expert. We perform a tools-based assessment which provides a comprehensive and thorough review of a company's environment and technology systems. In addition to the technology based functional requirements, the consultant also discusses and records the non-functional business requirements, challenges, and constraints. Assessments help organizations like yours, no matter how large or small, get a better return on your IT investment and overcome challenges in the ever-changing technology landscape.

- **Design Services**

Professional Services consultants perform infrastructure design and implementation planning to support your strategy. The high-level architectures provided by the assessment service are turned into low level designs and wiring diagrams, which are reviewed and approved prior to implementation. The implementation plan will demonstrate an outcome-based proposal to provide business capabilities through infrastructure with a risk-mitigated project plan.

## Lenovo Plan & Design Services

Unlock faster time to market with our tailored, strategic design workshops to align solution approaches with your business goals and technical requirements. Leverage our deep solution expertise and end-to-end delivery partnership to meet your goals efficiently and effectively.

## Lenovo Deployment, Migration, and Configuration Services

Optimize your IT operations by shifting labor-intensive functions to Lenovo's skilled technicians for seamless on-site or remote deployment, configuration, and migration. Enjoy peace of mind, faster time to value, and comprehensive knowledge sharing with your IT staff, backed by our best-practice methodology.

- **Deployment Services for Storage and ThinkAgile**

A comprehensive range of remote and onsite options tailored specifically for your business needs to ensure your storage and ThinkAgile hardware are fully operational from the start.

- **Hardware Installation Services**

A full-range, comprehensive setup for your hardware, including unpacking, inspecting, and positioning components to ensure your equipment is operational and error-free for the most seamless and efficient installation experience, so you can quickly benefit from your investments.

- **DM/DG File Migration Services**

Take the burden of file migration from your IT's shoulders. Our experts will align your requirements and business objectives to the migration plans while coordinating with your team to plan and safely execute the data migration to your storage platforms.

- **DM/DG/DE Health Check Services**

Our experts perform proactive checks of your Firmware and system health to ensure your machines are operating at peak and optimal efficiency to maximize up-time, avoid system failures, ensure the security of IT solutions and simplify maintenance.

- **Factory Integrated Services**

A suite of value-added offerings provided during the manufacturing phase of a server or storage system that reduces time to value. These services aim at improving your hardware deployment experience and enhance the quality of a standard configuration before it arrives at your facility.

## Lenovo Support Services

In addition to response time options for hardware parts, repairs, and labor, Lenovo offers a wide array of additional support services to ensure your business is positioned for success and longevity. Our goal is to reduce your capital outlays, mitigate your IT risks, and accelerate your time to productivity.

- **Premier Support for Data Centers**

Your direct line to the solution that promises the best, most comprehensive level of support to help you fully unlock the potential of your data center.

- **Premier Enhanced Storage Support (PESS)**

Gain all the benefits of Premier Support for Data Centers, adding dedicated storage specialists and resources to elevate your storage support experience to the next level.

- **Committed Service Repair (CSR)**

Our commitment to ensuring the fastest, most seamless resolution times for mission-critical systems that require immediate attention to ensure minimal downtime and risk for your business. This service is only available for machines under the Premier 4-Hour Response SLA.

- **Multivendor Support Services (MVS)**

Your single point of accountability for resolution support across vast range of leading Server, Storage, and Networking OEMs, allowing you to manage all your supported infrastructure devices seamlessly from a single source.

- **Keep Your Drive (KYD)**

Protect sensitive data and maintain compliance with corporate retention and disposal policies to ensure your data is always under your control, regardless of the number of drives that are installed in your Lenovo server.

- **Technical Account Manager (TAM)**

Your single point of contact to expedite service requests, provide status updates, and furnish reports to track incidents over time, ensuring smooth operations and optimized performance as your business grows.

- **Enterprise Software Support (ESS)**

Gain comprehensive, single-source, and global support for a wide range of server operating systems and Microsoft server applications.

For more information, consult the brochure [Lenovo Operational Support Services for Data Centers](#).

## Lenovo Managed Services

Achieve peak efficiency, high security, and minimal disruption with Lenovo's always-on Managed Services. Our real-time monitoring, 24x7 incident response, and problem resolution ensure your infrastructure operates seamlessly. With quarterly health checks for ongoing optimization and innovation, Lenovo's remote active monitoring boosts end-user experience and productivity by keeping your data center's hardware performing at its best.

Lenovo Managed Services provides continuous 24x7 remote monitoring (plus 24x7 call center availability) and proactive management of your data center using state-of-the-art tools, systems, and practices by a team of highly skilled and experienced Lenovo services professionals.

Quarterly reviews check error logs, verify firmware & OS device driver levels, and software as needed. We'll also maintain records of latest patches, critical updates, and firmware levels, to ensure you systems are providing business value through optimized performance.

## Lenovo Sustainability Services

- **Asset Recovery Services**

Lenovo Asset Recovery Services (ARS) provides a secure, seamless solution for managing end-of-life IT assets, ensuring data is safely sanitized while contributing to a more circular IT lifecycle. By maximizing the reuse or responsible recycling of devices, ARS helps businesses meet sustainability goals while recovering potential value from their retired equipment. For more information, see the [Asset Recovery Services offering page](#).

- **CO2 Offset Services**

Lenovo's CO2 Offset Services offer a simple and transparent way for businesses to take tangible action on their IT footprint. By integrating CO2 offsets directly into device purchases, customers can easily support verified climate projects and track their contributions, making meaningful progress toward their sustainability goals without added complexity.

- **Lenovo Certified Refurbished**

Lenovo Certified Refurbished offers a cost-effective way to support IT circularity without compromising on quality and performance. Each device undergoes rigorous testing and certification, ensuring reliable performance and extending its lifecycle. With Lenovo's trusted certification, you gain peace of mind while making a more sustainable IT choice.

## Regulatory compliance

The ThinkSystem DE Series enclosures conform to the following regulations:

- United States: FCC Part 15, Class A; UL 60950-1 and 62368-1
- Canada: ICES-003, Class A; CAN/CSA-C22.2 60950-1 and 62368-1
- Argentina: IEC60950-1
- Mexico NOM
- European Union: CE Mark (EN55032 Class A, EN55024, IEC/EN60950-1 and 62368-1); ROHS Directive 2011/65/EU
- Russia, Kazakhstan, Belarus: EAC
- China: CCC GB 4943.1, GB 17625.1, GB 9254 Class A; CELP; CECP
- India: BIS
- Japan: VCCI, Class A
- Taiwan: BSMI CNS 13438, Class A; CNS 14336-1
- Korea KN32/35, Class A
- Australia/New Zealand: AS/NZS CISPR 22 Class A



## Interoperability

Lenovo provides end-to-end storage compatibility testing to deliver interoperability throughout the network. The ThinkSystem DE4800H and DE4800F Hybrid and all-flash Storage Array supports attachment to Lenovo ThinkSystem, hosts by using SAS, iSCSI, Fibre Channel, storage connectivity protocols.

For end-to-end storage configuration support, refer to the Lenovo Storage Interoperation Center (LSIC): <https://datacentersupport.lenovo.com/us/en/lxic>

Use the LSIC to select the known components of your configuration and then get a list all other supported combinations, with details about supported hardware, firmware, operating systems, and drivers, plus any additional configuration notes. View results on screen or export them to Excel.

## Fibre Channel SAN switches

Lenovo offers the ThinkSystem DB Series of Fibre Channel SAN switches for high-performance storage expansion. See the DB Series product guides for models and configuration options:

- ThinkSystem DB Series SAN Switches:  
<https://lenovopress.com/storage/switches/rack#rt=product-guide>

## Rack cabinets

The following table lists the supported rack cabinets.

Table 23. Rack cabinets (D)

Model	Description
7D6DA007WW	ThinkSystem 42U Onyx Primary Heavy Duty Rack Cabinet (1200mm)
7D6DA008WW	ThinkSystem 42U Pearl Primary Heavy Duty Rack Cabinet (1200mm)
7D6EA009WW	ThinkSystem 48U Onyx Primary Heavy Duty Rack Cabinet (1200mm)
7D6EA00AWW	ThinkSystem 48U Pearl Primary Heavy Duty Rack Cabinet (1200mm)
93074RX	42U Standard Rack (1000mm)
93604PX	42U 1200mm Deep Dynamic Rack
93614PX	42U 1200mm Deep Static Rack
93634PX	42U 1100mm Dynamic Rack
93634EX	42U 1100mm Dynamic Expansion Rack

For specifications about these racks, see the Lenovo Rack Cabinet Reference, available from: <https://lenovopress.com/lp1287-lenovo-rack-cabinet-reference>

For more information, see the list of Product Guides in the Rack cabinets category: <https://lenovopress.com/servers/options/racks>

## Power distribution units

The following table lists the power distribution units (PDUs) that are offered by Lenovo.

Table 24. Power distribution units

Part number	Feature code	Description	ANZ	ASEAN	Brazil	EET	MEA	RUCIS	WE	HTK	INDIA	JAPAN	LA	NA	PRC
<b>0U Basic PDUs</b>															
4PU7A93176	C0QH	0U 36 C13 and 6 C19 Basic 32A 1 Phase PDU v2	Y	Y	Y	Y	Y	Y	Y	Y	Y	N	Y	Y	Y
4PU7A93177	C0QJ	0U 24 C13/C15 and 24 C13/C15/C19 Basic 32A 3 Phase WYE PDU v2	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
<b>0U Switched and Monitored PDUs</b>															
4PU7A93181	C0QN	0U 21 C13/C15 and 21 C13/C15/C19 Switched and Monitored 48A 3 Phase Delta PDU v2 (60A derated)	N	Y	N	N	N	N	N	Y	N	Y	N	Y	N
4PU7A93178	C0QK	0U 20 C13 and 4 C19 Switched and Monitored 32A 1 Phase PDU v2	Y	Y	Y	Y	Y	Y	Y	Y	Y	N	Y	Y	Y
4PU7A93171	C0D8	0U 20 C13 and 4 C19 Switched and Monitored 32A 1 Phase PDU	Y	Y	Y	Y	Y	Y	Y	Y	Y	N	Y	Y	Y
4PU7A93182	C0QP	0U 18 C13/C15 and 18 C13/C15/C19 Switched and Monitored 63A 3 Phase WYE PDU v2	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
4PU7A93175	C0CS	0U 18 C13/C15 and 18 C13/C15/C19 Switched and Monitored 63A 3 Phase WYE PDU	Y	Y	Y	Y	Y	Y	Y	Y	Y	N	Y	Y	Y
4PU7A93180	C0QM	0U 18 C13/C15 and 18 C13/C15/C19 Switched and Monitored 32A 3 Phase WYE PDU v2	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
4PU7A93179	C0QL	0U 16 C13/C15 and 16 C13/C15/C19 Switched and Monitored 24A 1 Phase PDU v2 (30A derated)	N	Y	N	N	N	N	N	Y	N	Y	N	Y	N
<b>1U Switched and Monitored PDUs</b>															
4PU7A90808	C0D4	1U 18 C19/C13 Switched and monitored 48A 3P WYE PDU V2 ETL	N	N	N	N	N	N	N	Y	N	Y	Y	Y	N
4PU7A81117	BNDV	1U 18 C19/C13 switched and monitored 48A 3P WYE PDU - ETL	N	N	N	N	N	N	N	N	N	N	N	Y	N
4PU7A90809	C0DE	1U 18 C19/C13 Switched and monitored 48A 3P WYE PDU V2 CE	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	N	Y
4PU7A90810	C0DD	1U 18 C19/C13 Switched and monitored 80A 3P Delta PDU V2	N	N	N	N	N	N	N	Y	N	Y	Y	Y	N
4PU7A90811	C0DC	1U 12 C19/C13 Switched and monitored 32A 3P WYE PDU V2	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
4PU7A90812	C0DB	1U 12 C19/C13 Switched and monitored 60A 3P Delta PDU V2	N	N	N	N	N	N	N	Y	N	Y	Y	Y	N
<b>Line cords for 1U PDUs that ship without a line cord</b>															
40K9611	6504	4.3m, 32A/380-415V, EPDU/IEC 309 3P+N+G 3ph wye (non-US) Line Cord	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
40K9612	6502	4.3m, 32A/230V, EPDU to IEC 309 P+N+G (non-US) Line Cord	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
40K9613	6503	4.3m, 63A/230V, EPDU to IEC 309 P+N+G (non-US) Line Cord	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y

Part number	Feature code	Description	ANZ	ASEAN	Brazil	EET	MEA	RUCIS	WE	HTK	INDIA	JAPAN	LA	NA	PRC
40K9614	6500	4.3m, 30A/208V, EPDU to NEMA L6-30P (US) Line Cord	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
40K9615	6501	4.3m, 60A/208V, EPDU to IEC 309 2P+G (US) Line Cord	N	N	Y	N	N	N	Y	N	N	Y	Y	Y	N

For more information, see the Lenovo Press documents in the PDU category:  
<https://lenovopress.com/servers/options/pdu>

## Uninterruptible power supply units

The following table lists the uninterruptible power supply (UPS) units that are offered by Lenovo.

Table 25. Uninterruptible power supply units

Part number	Description
Rack-mounted or tower UPS units - 100-125VAC	
7DD5A001WW	RT1.5kVA 2U Rack or Tower UPS-G2 (100-125VAC)
7DD5A003WW	RT3kVA 2U Rack or Tower UPS-G2 (100-125VAC)
Rack-mounted or tower UPS units - 200-240VAC	
7DD5A002WW	RT1.5kVA 2U Rack or Tower UPS-G2 (200-240VAC)
7DD5A005WW	RT3kVA 2U Rack or Tower UPS-G2 (200-240VAC)
7DD5A007WW	RT5kVA 3U Rack or Tower UPS-G2 (200-240VAC)
7DD5A008WW	RT6kVA 3U Rack or Tower UPS-G2 (200-240VAC)
7DD5A00AWW	RT11kVA 6U Rack or Tower UPS-G2 (200-240VAC)

† Only available in China and the Asia Pacific market.

For more information, see the list of Product Guides in the UPS category:  
<https://lenovopress.com/servers/options/ups>

## Lenovo Financial Services

Why wait to obtain the technology you need now? No payments for 90 days and predictable, low monthly payments make it easy to budget for your Lenovo solution.

- **Flexible**

Our in-depth knowledge of the products, services and various market segments allows us to offer greater flexibility in structures, documentation and end of lease options.

- **100% Solution Financing**

Financing your entire solution including hardware, software, and services, ensures more predictability in your project planning with fixed, manageable payments and low monthly payments.

- **Device as a Service (DaaS)**

Leverage latest technology to advance your business. Customized solutions aligned to your needs. Flexibility to add equipment to support growth. Protect your technology with Lenovo's Premier Support service.

- **24/7 Asset management**

Manage your financed solutions with electronic access to your lease documents, payment histories, invoices and asset information.

- **Fair Market Value (FMV) and \$1 Purchase Option Leases**

Maximize your purchasing power with our lowest cost option. An FMV lease offers lower monthly payments than loans or lease-to-own financing. Think of an FMV lease as a rental. You have the flexibility at the end of the lease term to return the equipment, continue leasing it, or purchase it for the fair market value. In a \$1 Out Purchase Option lease, you own the equipment. It is a good option when you are confident you will use the equipment for an extended period beyond the finance term. Both lease types have merits depending on your needs. We can help you determine which option will best meet your technological and budgetary goals.

Ask your Lenovo Financial Services representative about this promotion and how to submit a credit application. For the majority of credit applicants, we have enough information to deliver an instant decision and send a notification within minutes.

## Seller training courses

The following sales training courses are offered for employees and partners (login required). Courses are listed in date order.

1. **Lenovo Storage Sales Certification Exam Study Guide**

2025-09-12 | 10 minutes | Employees and Partners

This guide includes information to help candidates prepare and register for the Lenovo Storage Sales Certification Exam (LENU-123C).

Tags: Storage

Published: 2025-09-12

Length: 10 minutes

**Start the training:**

Employee link: [Grow@Lenovo](mailto:Grow@Lenovo)

Partner link: [Lenovo 360 Learning Center](#)

Course code: LENU-123C-SG

## 2. **How to Order DM and DE Services Through DCSC**

2025-08-28 | 35 minutes | Employees and Partners

The goal of this training is to provide Lenovo sellers and business partners with an overview of the available services for ThinkSystem DM and DE.

Learning Objectives:

- Review what is included in each service
- Describe the benefits of each service
- Demonstrate how to order
- Discover where to go for more details

Tags: Services

Published: 2025-08-28

Length: 35 minutes

### **Start the training:**

Employee link: [Grow@Lenovo](#)

Partner link: [Lenovo 360 Learning Center](#)

Course code: DSVC134r4

## 3. **Partner Technical Webinar - Commvault**

2025-08-11 | 60 minutes | Employees and Partners

In this 60-minute replay, Commvault provided an in-depth look into Hyperscale X, Bundles, IntelliSnap and licensing.

Tags: Data Management

Published: 2025-08-11

Length: 60 minutes

### **Start the training:**

Employee link: [Grow@Lenovo](#)

Partner link: [Lenovo 360 Learning Center](#)

Course code: AUG0825

## 4. **ThinkSystem DE Series Portfolio Overview**

2025-06-20 | 30 minutes | Employees and Partners

This course builds on the Data Storage Solutions Overview (DSTOO102) course by introducing you to the DE Series Portfolio. After completing this course, you will be able to position the Lenovo ThinkSystem DE Series products and features based on the needs of your customers, correlate the Lenovo ThinkSystem DE Series Portfolio with Lenovo's comprehensive Data Management Portfolio, and use the qualifying questions to identify customer needs during conversations.

Tags: Data Management, Storage, ThinkSystem

Published: 2025-06-20

Length: 30 minutes

### **Start the training:**

Employee link: [Grow@Lenovo](#)

Partner link: [Lenovo 360 Learning Center](#)

Course code: DDEO101

## 5. Data Storage Solutions Overview

2025-06-18 | 25 minutes | Employees and Partners

After completing this course you will be able to:

1. Know more about the data management trends and challenges
2. Understand the data storage solutions portfolio
3. Find out how data drives business value

Tags: Storage

Published: 2025-06-18

Length: 25 minutes

### Start the training:

Employee link: [Grow@Lenovo](#)

Partner link: [Lenovo 360 Learning Center](#)

Course code: DSTOO102

## 6. Lenovo Data Center Product Portfolio

2025-06-11 | 20 minutes | Employees and Partners

This course introduces the Lenovo data center portfolio, and covers servers, storage, storage networking, and software-defined infrastructure products. After completing this course about Lenovo data center products, you will be able to identify product types within each data center family, describe Lenovo innovations that this product family or category uses, and recognize when a specific product should be selected.

Course objectives:

1. Identify product types within each data center family
2. Describe the features of the product family or category
3. Recognize when a specific product should be selected

Tags: Advanced DataCenter, DataCenter Products, Server, ThinkAgile, ThinkEdge, ThinkSystem

Published: 2025-06-11

Length: 20 minutes

### Start the training:

Employee link: [Grow@Lenovo](#)

Partner link: [Lenovo 360 Learning Center](#)

Course code: SXXW1110r8

## 7. **Partner Technical Webinar - DB710S & DE Announcements**

2025-05-13 | 60 minutes | Employees and Partners

This 60-minute replay concludes the storage announcement series update with DE and DB710S. During this session, we covered the latest advancements in storage technology, discussed the performance improvements and new features of DE, and explored the capabilities and benefits of the updated DB710S.

Tags: DataCenter Products, Storage

Published: 2025-05-13

Length: 60 minutes

### **Start the training:**

Employee link: [Grow@Lenovo](#)

Partner link: [Lenovo 360 Learning Center](#)

Course code: MAY0925

## 8. **Family Portfolio: Storage**

2025-04-30 | 50 minutes | Employees and Partners

This course covers the Lenovo storage portfolio, from tape drives used for backups and archiving all the way through high-performance storage systems. After completing this course about the Storage family, the learner will be able to identify products and features within the family, describe the features of this Product Family, and recognize when a specific product should be selected.

Tags: Storage, ThinkSystem

Published: 2025-04-30

Length: 50 minutes

### **Start the training:**

Employee link: [Grow@Lenovo](#)

Partner link: [Lenovo 360 Learning Center](#)

Course code: SXSW1201r17

## 9. **Partner Technical Webinar - Cost Effective Storage Solutions**

2025-01-14 | 60 minutes | Employees and Partners

In this 60-minute replay, Lenovo Storage Architect, Dan Beins presented Lenovo's strategy, capabilities, and portfolio for Data Management. Dan did a super job going beyond the product feature / function and talking about where our products bring value to our customer's Data Management.

Tags: Data Management

Published: 2025-01-14

Length: 60 minutes

### **Start the training:**

Employee link: [Grow@Lenovo](#)

Partner link: [Lenovo 360 Learning Center](#)

Course code: 011025

#### 10. **ThinkSystem DE Series: Hardware Specifications**

2024-12-30 | 25 minutes | Employees and Partners

This course also explores the unique data management features of the ThinkSystem SAN Manager. Course DDET200 Positioning ThinkSystem DE Series is recommended prior to this course.

By the end of this course, you should be able to:

- Identify the controller and expansion models of the Lenovo DE Series portfolio
- Explain the connectivity options, expansion paths, and cabling for the DE Series storage system
- Describe the data management features of Lenovo ThinkSystem SAN Manager

Tags: Data Management, Storage, Technical Sales, ThinkSystem

Published: 2024-12-30

Length: 25 minutes

##### **Start the training:**

Employee link: [Grow@Lenovo](mailto:Grow@Lenovo)

Partner link: [Lenovo 360 Learning Center](#)

Course code: DDET201r3

#### 11. **ThinkSystem DM and DE Series Technical Overview**

2024-10-15 | 30 minutes | Employees and Partners

This course provides a technical overview of the ThinkSystem DM and DE series products. Course DDMO101 – Lenovo ThinkSystem DM & DE Series Overview is recommended prior to this course.

By the end of this course, you should be able to:

- Describe the Lenovo portfolio for the DM and DE storage systems
- Explain features of the DM series ONTAP software
- Explain features of the ThinkSystem SAN Manager

Tags: Data Management, Storage

Published: 2024-10-15

Length: 30 minutes

##### **Start the training:**

Employee link: [Grow@Lenovo](mailto:Grow@Lenovo)

Partner link: [Lenovo 360 Learning Center](#)

Course code: DDMT100r2



12. **VTT Data Management How to sell storage - April 2024**  
2024-04-10 | 60 minutes | Employees and Partners

In this course, you will know:

- Why do we sell storage?
- What are the basics you need to get an opportunity rolling?
- Why Lenovo for Storage?
- What is happening in the market today?
- How to determine traction?

Tags: Data Management, Storage

Published: 2024-04-10

Length: 60 minutes

**Start the training:**

Employee link: [Grow@Lenovo](mailto:Grow@Lenovo)

Partner link: [Lenovo 360 Learning Center](#)

Course code: DVDAT209

13. **Lenovo Data Backup and Recovery Solution Overview**  
2024-03-25 | 40 minutes | Employees and Partners

The goal of this course is to give Lenovo sellers and business partners an overview of the Data Backup and Recovery solution. This course includes general information about backup, archive, disaster, nomenclature and key terms for back and recovery, and Lenovo features and alliance partners software.

Tags: Data Management

Published: 2024-03-25

Length: 40 minutes

**Start the training:**

Employee link: [Grow@Lenovo](mailto:Grow@Lenovo)

Partner link: [Lenovo 360 Learning Center](#)

Course code: DSOLO200

14. **Positioning ThinkSystem DE Series**  
2024-02-01 | 12 minutes | Employees and Partners

This course provides details on how to position DE series storage systems. Course DDMO101 – Lenovo ThinkSystem DM & DE Series Overview is a prerequisite.

This course focuses on enabling you to:

- Describe the features and business value of DE Series products
- Identify customer problems that DE Series products can solve
- Position the appropriate DE Series product for each customer

Tags: Storage, ThinkSystem

Published: 2024-02-01

Length: 12 minutes

**Start the training:**

Employee link: [Grow@Lenovo](mailto:Grow@Lenovo)

Partner link: [Lenovo 360 Learning Center](#)

Course code: DDET200r2

15. **Using VEEAM with ThinkSystem DE Series**

2023-10-03 | 10 minutes | Employees and Partners

In this course you will learn about VEEAM Availability Suite for ThinkSystem DE Series. By the end of this course, you will identify the advantages of using Veeam Availability Suite and Lenovo DE Series, describe the Veeam Cloud Connect Backup with Lenovo DE Series, and explain how to use Veeam's capabilities to provide deduplication and Compression with DE Series. Last updated on September, 29th, 2023.

Tags: ThinkSystem

Published: 2023-10-03

Length: 10 minutes

**Start the training:**

Employee link: [Grow@Lenovo](mailto:Grow@Lenovo)

Partner link: [Lenovo 360 Learning Center](#)

Course code: DSTOO200

16. **Assessment for Lenovo ThinkSystem DM and DE Series Technical Overview 100**

2023-10-02 | 30 minutes | Partners Only

This is the online assessment for the virtual-live course Lenovo ThinkSystem DM and DE Series Technical Overview 100 (DDMT100).

Your objective for this assessment is to complete the 15-question quiz with the minimum passing score of 80%.

Tags: Technical Sales

Published: 2023-10-02

Length: 30 minutes

**Start the training:**

Partner link: [Lenovo 360 Learning Center](#)

Course code: DDMT101

17. **ThinkSystem DE Series: Technical Overview Assessment 200**

2023-09-28 | 10 minutes | Employees and Partners

This document contains assessment questions that focus on ThinkSystem DE Series technology. The questions are based on the Lenovo ThinkSystem DE Series Technical Overview curriculum.

Tags: Sales, Storage, Technical Sales, ThinkSystem

Published: 2023-09-28

Length: 10 minutes

**Start the training:**

Employee link: [Grow@Lenovo](mailto:Grow@Lenovo)

Partner link: [Lenovo 360 Learning Center](#)

Course code: DDET207

18. **ThinkSystem DE Series: Storage System Configuration**

2023-09-28 | 23 minutes | Employees and Partners

This course describes the differences between the Volume Groups and Dynamic Disk Pools technologies, as well as the benefits and tradeoffs of using each. Course DDET201 ThinkSystem DE Series: Hardware Specifications is a prerequisite.

Upon completion of this training, you will be able to:

- Distinguish volume groups from dynamic disk pools
- Determine when to use volume groups and when to use Dynamic Disk Pools (DDP) technology
- Describe DDP technology and its benefits
- Describe volume groups and their benefits
- Explain how the thin-provisioning feature provides value

Tags: Data Management, Storage, Technical Sales, ThinkSystem

Published: 2023-09-28

Length: 23 minutes

**Start the training:**

Employee link: [Grow@Lenovo](#)

Partner link: [Lenovo 360 Learning Center](#)

Course code: DDET202

19. **ThinkSystem DE Series: SSD Cache**

2023-09-28 | 15 minutes | Employees and Partners

This course describes the SSD Cache feature and how SSD Cache helps to optimize read operations. Course DDET202 ThinkSystem DE Series: Storage System Configuration is a prerequisite.

Upon completion of this training, you will be able to:

- Describe the SSD Cache feature
- Explain how SSD Cache helps you optimize solid-state disk (SSD) read cache in a DE Series storage system

Tags: Data Management, Storage, Technical Sales, ThinkSystem

Published: 2023-09-28

Length: 15 minutes

**Start the training:**

Employee link: [Grow@Lenovo](#)

Partner link: [Lenovo 360 Learning Center](#)

Course code: DDET203

20. **VEEAM Solutions Sales Training**

2023-09-27 | 20 minutes | Employees and Partners

In this course you will learn about Hyper-availability for the Always-On Enterprise.

By the end of this training, you should be able to:

Identify and explain the core products and solutions offered by Veeam.

Explain the key benefits and value propositions of integrating Veeam solutions with Lenovo products.

Tags: Sales

Published: 2023-09-27

Length: 20 minutes

**Start the training:**

Employee link: [Grow@Lenovo](mailto:Grow@Lenovo)

Partner link: [Lenovo 360 Learning Center](#)

Course code: DSTOO100

21. **ThinkSystem DE Series: Disaster Recovery**

2023-09-21 | 28 minutes | Employees and Partners

This course describes technologies for disaster recovery and how DE series features can contribute in substantial ways to any disaster-recovery plan for storage.

Tags: ThinkSystem

Published: 2023-09-21

Length: 28 minutes

**Start the training:**

Employee link: [Grow@Lenovo](mailto:Grow@Lenovo)

Partner link: [Lenovo 360 Learning Center](#)

Course code: DDET204

22. **Selling ThinkSystem DE Series**

2022-09-15 | 15 minutes | Employees and Partners

This course discusses common selling scenarios that describe where and how to sell Thinksystem DE series storage systems.

This course focuses on enabling you to:

- Discuss storage configurations and the advantages of each configuration
- Review use cases to identify what customers need from storage systems
- Suggest storage configurations that meet customer needs

Tags: Sales, Storage, Technical Sales, ThinkSystem

Published: 2022-09-15

Length: 15 minutes

**Start the training:**

Employee link: [Grow@Lenovo](mailto:Grow@Lenovo)

Partner link: [Lenovo 360 Learning Center](#)

Course code: DDET206r2

## Related publications and links

For more information, see the following resources:

- Lenovo SAN Storage product page  
<https://www.lenovo.com/us/en/c/data-center/storage/storage-area-network>
- ThinkSystem DE Hybrid Storage interactive 3D Tour  
<https://lenovopress.com/lp0957-thinksystem-de-hybrid-interactive-3d-tour>
- ThinkSystem DE Hybrid Storage datasheet  
<https://lenovopress.com/ds0049-lenovo-thinksystem-de-series-hybrid-array>
- Lenovo Data Center Solution Configurator  
<http://dcsc.lenovo.com>
- Lenovo Data Center Support  
<http://datacentersupport.lenovo.com>

## Related product families

Product families related to this document are the following:

- [DE Series Storage](#)
- [External Storage](#)
- [Lenovo SAN Storage](#)

## Notices

Lenovo may not offer the products, services, or features discussed in this document in all countries. Consult your local Lenovo representative for information on the products and services currently available in your area. Any reference to a Lenovo product, program, or service is not intended to state or imply that only that Lenovo product, program, or service may be used. Any functionally equivalent product, program, or service that does not infringe any Lenovo intellectual property right may be used instead. However, it is the user's responsibility to evaluate and verify the operation of any other product, program, or service. Lenovo may have patents or pending patent applications covering subject matter described in this document. The furnishing of this document does not give you any license to these patents. You can send license inquiries, in writing, to:

Lenovo (United States), Inc.  
8001 Development Drive  
Morrisville, NC 27560  
U.S.A.  
Attention: Lenovo Director of Licensing

LENOVO PROVIDES THIS PUBLICATION "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions, therefore, this statement may not apply to you.

This information could include technical inaccuracies or typographical errors. Changes are periodically made to the information herein; these changes will be incorporated in new editions of the publication. Lenovo may make improvements and/or changes in the product(s) and/or the program(s) described in this publication at any time without notice.

The products described in this document are not intended for use in implantation or other life support applications where malfunction may result in injury or death to persons. The information contained in this document does not affect or change Lenovo product specifications or warranties. Nothing in this document shall operate as an express or implied license or indemnity under the intellectual property rights of Lenovo or third parties. All information contained in this document was obtained in specific environments and is presented as an illustration. The result obtained in other operating environments may vary. Lenovo may use or distribute any of the information you supply in any way it believes appropriate without incurring any obligation to you.

Any references in this publication to non-Lenovo Web sites are provided for convenience only and do not in any manner serve as an endorsement of those Web sites. The materials at those Web sites are not part of the materials for this Lenovo product, and use of those Web sites is at your own risk. Any performance data contained herein was determined in a controlled environment. Therefore, the result obtained in other operating environments may vary significantly. Some measurements may have been made on development-level systems and there is no guarantee that these measurements will be the same on generally available systems. Furthermore, some measurements may have been estimated through extrapolation. Actual results may vary. Users of this document should verify the applicable data for their specific environment.

© Copyright Lenovo 2025. All rights reserved.

This document, LP2072, was created or updated on September 24, 2025.

Send us your comments in one of the following ways:

- Use the online Contact us review form found at:  
<https://lenovopress.lenovo.com/LP2072>
- Send your comments in an e-mail to:  
[comments@lenovopress.com](mailto:comments@lenovopress.com)

This document is available online at <https://lenovopress.lenovo.com/LP2072>.

## Trademarks

Lenovo and the Lenovo logo are trademarks or registered trademarks of Lenovo in the United States, other countries, or both. A current list of Lenovo trademarks is available on the Web at <https://www.lenovo.com/us/en/legal/copytrade/>.

The following terms are trademarks of Lenovo in the United States, other countries, or both:

Lenovo®

ThinkAgile®

ThinkSystem®

XClarity®

The following terms are trademarks of other companies:

Linux® is the trademark of Linus Torvalds in the U.S. and other countries.

Microsoft®, Excel®, Georgia®, Windows Server®, and Windows® are trademarks of Microsoft Corporation in the United States, other countries, or both.

IBM® is a trademark of IBM in the United States, other countries, or both.

Other company, product, or service names may be trademarks or service marks of others.