



FusionServer

# 1288 V8 Rack Server

Exceptional Computing | Outstanding Security  
Optimal Energy Efficiency



XFUSION INTERNATIONAL PTE. LTD.

# Rack Server

## FusionServer 1288 V8

### Introduction



1288 V8 (10 drives)

The FusionServer 1288 V8 is a next-generation 1U2P rack server specifically designed to meet the demands of virtualization, High-Performance Computing (HPC), and Office Automation (OA). Its compact design, solid reliability, and ease of management and deployment make it an ideal choice for dealing with business requirements in industries such as Internet, government and enterprise, and finance.

### Highlights



#### Exceptional Computing

- **Compact Deployment:** 1U space for 2 x Intel® Xeon® 6 processors, with up to 144 cores and a maximum TDP of 350 W per processor; 32 x memory slots available for DDR5 DIMMs at up to 6400 MT/s or MRDIMMs at up to 8000 MT/s
- **Fast Storage:** 10 x 2.5" SAS/SATA/NVMe drives, 4 x 3.5" SAS/SATA drives\*, or 16 x E3.S SSDs\*
- **Powerful Scalability:** up to 5 x PCIe 5.0 slots at the rear, including 2 x OCP 3.0 slots



#### Outstanding Security

- **Enhanced Maintenance Efficiency:** quick, precise PCIe link fault diagnosis, boosting efficiency by 50%
- **Reduced System Downtime:** industry-exclusive AI memory self-healing, with precise memory link diagnosis, cutting downtime by 66%



#### Optimal Energy Efficiency

- **Dynamic Energy Management Technology:** intelligent, non-disruptive tuning based on workloads, achieving peak energy efficiency without rebooting
- **Industry-Leading Power Technology:** 97% power conversion efficiency, driven by three core innovations, setting the benchmark

\*Configuration details are subject to the technical white paper


# Rack Server

## FusionServer 1288 V8

### Technical Specifications

<b>Form Factor</b>	1U rack server
<b>Processor</b>	2 x Intel® Xeon® 6700P/6500P/6700E processors, each with up to 350 W TDP
<b>Memory</b>	32 x memory slots available for DDR5 DIMMs at up to 6400 MT/s or MRDIMMs at up to 8000 MT/s
<b>Local Storage</b>	Hot-swappable drive configurations: <ul style="list-style-type: none"> <li>- 8/10 x 2.5" SAS/SATA/NVMe drives</li> <li>- 4 x 3.5" SAS/SATA drives*</li> <li>- 16 x E3.S SSDs*</li> <li>- 2 x M.2 SSDs, supporting hardware RAID</li> </ul>
<b>RAID</b>	RAID 0, 1, 10, 5, 50, 6, and 60; supercapacitors for cache data protection from power failures; RAID level migration, drive roaming, self-diagnosis, and remote web-based configuration
<b>Network</b>	2 x hot-swappable OCP 3.0 NICs, supporting PCIe 5.0, NCSI, and multi-host
<b>PCIe Expansion</b>	Up to 5 x PCIe slots at the rear, supporting PCIe 5.0
<b>Fan</b>	8 x hot-swappable counter-rotating fans in N+1 redundancy
<b>PSU</b>	900 W/1500 W/2000 W/3000 W Platinum/Titanium hot-swappable PSUs in 1+1 redundancy
<b>Management</b>	<ul style="list-style-type: none"> <li>- The iBMC chip integrates one dedicated management GE port, providing comprehensive management features such as fault diagnosis, automatic O&amp;M, and hardware security hardening.</li> <li>- The iBMC supports standard interfaces such as Redfish, SNMP, and IPMI 2.0, provides a remote management user interface based on HTML5/VNC KVM, and supports out-of-band management functions such as monitoring, diagnosis, configuration, Agentless, and remote control for simplified management.</li> <li>- It is optional to configure FusionDirector that enables intelligent, automatic, visualized, and refined management throughout the server lifecycle.</li> </ul>
<b>OS</b>	Microsoft Windows Server, SUSE Linux Enterprise Server, VMware ESXi, Red Hat Enterprise Linux, Oracle, Ubuntu, and openEuler
<b>Security</b>	Power-on password, administrator password, Trusted Platform Module (TPM) 2.0, security bezel, secure boot, and chassis intrusion detection
<b>Operating Temperature</b>	5°C to 45°C (41°F to 113°F), compliant with ASHRAE Class A1/A2/A3/A4
<b>Installation Suite</b>	L-shaped guide rails, adjustable guide rails, and holding rails
<b>Dimensions (H x W x D)</b>	43 mm x 447 mm x 798 mm (1.69 in. x 17.60 in. x 31.42 in.)

\*Configuration details are subject to the technical white paper



**Copyright ©xFusion International Pte. Ltd. 2026. All rights reserved.**

No part of this document may be reproduced or transmitted in any form or by any means without prior written consent of xFusion International Pte. Ltd.

#### **Trademarks and Permissions**

**xFUSION** and other xFusion trademarks are trademarks of xFusion International Pte. Ltd. All other trademarks and trade names mentioned in this document are the property of their respective holders.

#### **Notice**

In this document, "xFusion" is used to refer to "xFusion International Pte. Ltd." for concise description and easy understanding, which does not mean that "xFusion" may have any other meaning. Any "xFusion" mentioned or described hereof may not be understood as any meaning other than "xFusion International Pte. Ltd.", and xFusion International Pte. Ltd. shall not bear any liability resulting from the use of "xFusion".

The purchased products, services and features are stipulated by the contract made between xFusion and the customer. All or part of the products, services and features described in this document may not be within the purchase scope or the usage scope. Unless otherwise specified in the contract, all statements, information, and recommendations in this document are provided "AS IS" without warranties, guarantees or representations of any kind, either express or implied.

The information in this document is subject to change without notice. Every effort has been made in the preparation of this document to ensure accuracy of the contents, but all statements, information, and recommendations in this document do not constitute a warranty of any kind, express or implied.